

Item no.: 385428

UPOINT 404A-T - 4-port industrial-grade USB 3.2 hubs, -40 to 85C operating temperature

from **335,50 EUR**

Item no.: 385428
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

The UPOINT series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPOINT Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions.

4-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature

USB Interface- USB Standards USB 3.2 Gen 1 USB 1.1/2.0 compliant- Speed 5 Gbps- USB Connector UFP: type B DFP: type A- No. of USB Ports 5 (UFP: 1, DFP 4)

Power Parameters- Input Voltage 12 to 48 VDC

No. of power inputs: 2- **Power Connector** Power jack 3-pin terminal block- **Reverse Polarity Protection Supported-** Input Current 2..8 A @ 12 VDC- **Output Power Rating** Port 1: 900 mA / 1500 mA @ 5 VDC, BC 1.2 compliant Rest of ports: 900 mA @ 5 VDC

Physical Characteristics- Housing Metal- **Dimensions** 85 x 27 x 100 mm (3.35 x 1.06 x 3.94 in)- **Weight** 264 g (0.58 lb)- **Installation** Wall mounting (with optional kit) DIN-rail mounting (with optional kit)

Environmental Limits- Operating Temperature -40 to 85°C (-40 to 185°F)- **Storage Temperature (package included)** -40 to 85°C (-40 to 185°F)- **Ambient Relative Humidity** 5 to 95% (non-condensing)

Standards and Certifications- EMC EN 55032/35- **EMI** CISPR 32, FCC Part 15B Class A- **EMS** IEC 61000-4-2 **ESD:** Contact: 8 kV; Air: 15 kV IEC 61000-4-3 **RS:** 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 **EFT:** Power: 2 kV IEC 61000-4-5 **Surge:** Power: 2 kV IEC 61000-4-6 **CS:** 150 kHz to 80 MHz: 10 V/m IEC 61000-4-8 **PFMF- Safety** EN 62368-1UL 62368-1KC- **Environmental Testing** IEC 60068-2-1- **Freefall** IEC 60068-2-34

Declaration- Green Product RoHS, CRoHS, WEEE MTBF- **Standards** Telcordia (Bellcore), GB- **Time** 2,107,973 hrs

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

