

Item no.: 385427

## UPOINT 404A - USB 3.2 hubs with 4 ports for industrial use

from **252,98 EUR**

Item no.: 385427  
 shipping weight: 0.20 kg  
 Manufacturer: MOXA



### Product Description

The USB hubs in the UPort series are industrial-grade and have been developed with the robustness and reliability required for industrial applications. Each port has level 4 ESD protection and offers super-speed USB 3.2 data rates of up to 5 Gbps - even for heavy-duty applications. The UPort series includes models with dual power inputs, DIN rail mounting options and wide temperature range models that operate reliably in harsh environments.

**4-Port USB 3.2 hubs in industrial quality, operating temperature from 0 to 60 °C**

**USB interface- USB standards** USB 3.2 Gen 1 USB 1.1/2.0 compliant- **Speed** 5 Gbps- **USB port** UFP: Type B DFP: Type A- **Number of USB ports** 5 (UFP: 1, DFP 4)

**Power parameters- Input voltage** 12 to 48 VDC **Number of power inputs:** 2- **Power connection** Power socket 3-pin terminal block- **Reverse polarity protection supported-** **Input current** 2.8 A @ 12 VDC- **Output power** Port 1: 900 mA / 1500 mA @ 5 VDC, BC 1.2 compliant Remaining ports: 900 mA @ 5 VDC

**Physical characteristics- Housing metal- Dimensions** 85 x 27 x 100 mm (3.35 x 1.06 x 3.94 in)- **Weight** 264 g (0.58 lb)- **Installation** Wall mounting (with optional kit) DIN rail mounting (with optional kit)

**Ambient conditions- Operating temperature** 0 to 60°C (32 to 140°F)- **Storage temperature (including packaging)** -20°C (32 to 140°F) **Storage temperature (including packaging)** -20 to 75°C (-4 to 167°F)- **Ambient relative humidity** 5 to 95% (non-condensing)

**Standards and certifications- EMC** EN 55032/35- **EMI** CISPR 32, FCC Part 15B Class A- **EMS** IEC 61000-4-2 **ESD: Contact:** 8 kV; **Air:** 15 kV IEC 61000-4-3 **RS:** 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 **EFT: Power:** 2 kV IEC 61000-4-5 **Surge: Power:** 2 kV IEC 61000-4-6 **CS:** 150 kHz to 80 MHz: 10 V/m IEC 61000-4-8 **PFMF-Safety** EN 62368-1UL 62368-1KC- **Environmental testing** IEC 60068-2-1- **Free fall** IEC 60068-2-34

**Declaration- Environmentally friendly product** RoHS, CRoHS, WEEE MTBF- **Time** 2.107.973 hours- **Standards** Telcordia (Bellcore), GB

### Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

