

Item no.: 385427

UPOINT 404A - USB 3.2 hubs with 4 ports for industrial use

from **231,30 EUR**

Item no.: 385427
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

The USB hubs in the UPort series are industrial-grade and have been developed with the robustness and reliability required for industrial applications. Each port has level 4 ESD protection and offers super-speed USB 3.2 data rates of up to 5 Gbps - even for heavy-duty applications. The UPort series includes models with dual power inputs, DIN rail mounting options and wide temperature range models that operate reliably in harsh environments. 4-Port USB 3.2 hubs in industrial quality, operating temperature from 0 to 60 °C USB interface- USB standards USB 3.2 Gen 1 USB 1.1/2.0 compliant- Speed 5 Gbps- USB port UFP: Type B DFP: Type A- Number of USB ports 5 (UFP: 1, DFP 4) Power parameters- Input voltage 12 to 48 VDC Number of power inputs: 2- Power connection Power socket 3-pin terminal block- Reverse polarity protection supported- Input current 2.8 A @ 12 VDC- Output power Port 1: 900 mA / 1500 mA @ 5 VDC, BC 1.2 compliant Remaining ports: 900 mA @ 5 VDC Physical characteristics- Housing metal- Dimensions 85 x 27 x 100 mm (3.35 x 1.06 x 3.94 in)- Weight 264 g (0.58 lb)- Installation Wall mounting (with optional kit) DIN rail mounting (with optional kit) Ambient conditions- Operating temperature 0 to 60 °C (32 to 140 °F)- Storage temperature (including packaging)-20 °C (32 to 140 °F) Storage temperature (including packaging)-20 to 75 °C (-4 to 167 °F)- Ambient relative humidity 5 to 95% (non-condensing) Standards and certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m IEC 61000-4-8 PFMF- Safety EN 62368-1 UL 62368-1 KC- Environmental testing IEC 60068-2-1- Free fall IEC 60068-2-34 Declaration- Environmentally friendly product RoHS, CRoHS, WEEE MTBF- Time 2.107.973 hours- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

