

Item no.: 385422 UPORT 204 - 4-port entry-level USB hub, adaptor included

from 173,75 EUR Item no.: 385422

shipping weight: 0.20 kg Manufacturer: MOXA



Product Description

The UPort series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPort Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions.4-port entry-level USB hub, adaptor includedUSB Interface- Speed 12 Mbps, 480 Mbps- USB Connector USB Type B- USB Standards USB 1.1/2.0 compliant- No. of USB Ports 4Power Parameters- Input Voltage 12 to 40 VDC- Input Current 1.21 A @ 12 VDCPhysical Characteristics-Housing Polycarbonate (PC)- Dimensions 70 x 35 x 120 mm (2.76 x 1.38 x 4.72 in) - Weight Packaged: 805 g (1.77 lb)Product only: 800 g (1.76 lb)Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -20 to 75°C (-4 to 167°F)Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMSIEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/mIEC 61000-4-4 EFT: Power: 2 kVIEC 61000-4-5 Surge: Power: 1 kVIEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/mIEC 61000-4-8 PFMF- Environmental TestingIEC 60068-2-3- Freefall IEC 60068-2-34Declaration-Green Product RoHS, CRoHS, WEEEMTBF- Time 1,577,573 hrs- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product All details, up-to-date prices and availability

