

Item no.: 385422

UPOINT 204 - 4-port entry-level USB hub, adaptor included

from **155,12 EUR**

Item no.: 385422
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

The UPoint series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPoint Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions. 4-port entry-level USB hub, adaptor included
USB Interface- Speed 12 Mbps, 480 Mbps- USB Connector USB Type B- USB Standards USB 1.1/2.0 compliant- No. of USB Ports 4
Power Parameters- Input Voltage 12 to 40 VDC- Input Current 1.21 A @ 12 VDC
Physical Characteristics- Housing Polycarbonate (PC)- Dimensions 70 x 35 x 120 mm (2.76 x 1.38 x 4.72 in)- Weight Packaged: 805 g (1.77 lb) Product only: 800 g (1.76 lb)
Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -20 to 75°C (-4 to 167°F)
Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/m IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1 IEC 60068-2-3- Freefall IEC 60068-2-34
Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 1,577,573 hrs- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

