

Item no.: 385430

UPOINT 404-T W/O ADAPTER - 4-port industrial USB hub, without adapter, -40 to 85C operating temperature

from **275,06 EUR**

Item no.: 385430
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

The UPort series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPort Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions.

4-port industrial USB hub, -40 to 85°C operating temperature
 USB Interface- Speed 12 Mbps, 480 Mbps- USB Connector USB Type B- USB Standards USB 1.1/2.0 compliant- No. of USB Ports 4
 Power Parameters- Input Current 1.3 A @ 12 VDC- Input Voltage 12 to 40 VDC
 Physical Characteristics- Housing Aluminum- Dimensions 80 x 35 x 130 mm (3.15 x 1.38 x 5.12 in)- Weight Packaged: 855 g (1.88 lb) Product only: 850 g (1.87 lb)- Installation Wall mounting, DIN-rail mounting (optional)
 Environmental Limits- Operating Temperature -40 to 85°C (-40 to 185°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)
 Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/m IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1- Safety UL 508- Freefall IEC 60068-2-34
 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 1,490,340 hrs- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

