

Item no.: 385426

UPOINT 404 - Industrial USB hub with 4 ports, including adapter

from **242,51 EUR**

Item no.: 385426
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

The USB hubs in the UPort series are industrial-grade and have been developed with the robustness and reliability required for industrial applications. Each port has level 4 ESD protection and offers super-speed USB 3.2 data rates of up to 5 Gbps - even for heavy-duty applications. The UPort series includes dual power input models, DIN rail mounting options and wide temperature range models that operate reliably in harsh environments. 4-port USB hub for industrial use, incl. adapter, operating temperature from 0 to 60°C USB interface- speed -12Mbps, 480 Mbps- USB port -USB type B- USB standards-USB 1.1/2.0 compliant- no. of USB ports-4 Performance parameters USB ports-4 Performance parameters- Input current -1.3 A @ 12 VDC- Input voltage-12 to 40 VDC Physical properties- Housing -Aluminium- Dimensions -80x 35 x 130 mm (3.15 x 1.38 x 5.12 in)- WeightPackaged: 855 g (1.88 lb)Product only: 850 g (1.87 lb)- Installation -Wall mount, DIN rail mount (optional)Environmental conditions- Operating temperature -0to 60°C (32 to 140°F)- Storage temperature (including packaging) --20 to 75°C (-4 to 167°F)- Relative humidity -5 to 95% (non-condensing)Standards and certifications- EMC -EN55032/24-EMI-CISPR 32, FCC Part 15B Class A- EMSIEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/mIEC 61000-4-4 EFT: Power: 2 kVIEC 61000-4-5 Surge: Power: 1 kVIEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/mIEC 61000-4-8 PFMF- Environmental tests-IEC60068-2-1- Safety-UL 508- Free-fall-IEC 60068-2-34Declaration- Environmentally friendly product -RoHS, CRoHS, WEEEMTBF- Time -1.490,340 hours- Standards -Telcordia(Bellcore), GB

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

