

Item no.: 385518

UPOINT 407A-T - USB 3.2 hubs with 7 ports for industrial use

from **390,49 EUR**

Item no.: 385518
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

The USB hubs in the UPort series are industrial-grade and have been developed with the robustness and reliability required for industrial applications. Each port has level 4 ESD protection and offers super-speed USB 3.2 data rates of up to 5 Gbps - even for heavy-duty applications. The UPort series includes models with dual power inputs, DIN rail mounting options and wide temperature range models that operate reliably in harsh environments.

7-Port USB 3.2 hubs in industrial quality, -40 to 85°C operating temperature

USB interface: USB standards USB 3.2 Gen 1 USB 1.1/2.0 compliant - Speed 5 Gbps - USB port UFP: Type B DFP: Type A - Number of USB ports 8 (UFP: 1, DFP 7)

Power parameters: Input voltage 12 to 48 VDC Number of power inputs: 2 - Power connection Power socket 3-pin terminal block - Reverse polarity protection supported - Input current 4.75 A @ 12 VDC - Output power Port 1: 900 mA / 1500 mA @ 5 VDC, BC 1.2 compliant Remaining ports: 900 mA @ 5 VDC

Physical characteristics: Housing metal - Dimensions 80 x 27 x 140 mm (3.15 x 1.06 x 5.51 in) - Weight 350 g (0.77 lb) - Installation Wall mounting (with optional kit) DIN rail mounting (with optional kit)

Environmental conditions: Operating temperature -40 to 85°C (-40 to 185°F) - Storage temperature (including packaging) -40 to 185°F (-40 to 185°C) Storage temperature (including packaging) -40 to 85°C (-40 to 185°F) - Ambient relative humidity 5 to 95% (non-condensing)

Standards and certifications: EMC EN 55032/35 - EMI CISPR 32, FCC Part 15B Class A - EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m IEC 61000-4-8 PFMF - Safety EN 62368-1 UL 62368-1 KC - Environmental testing IEC 60068-2-1 - Free fall IEC 60068-2-34 Declaration - Environmentally friendly product RoHS, CRoHS, WEEE MTBF - Standards Telcordia (Bellcore), GB - Time 1.467,922 hrs.

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

