

Item no.: 385514

UPOINT 207 - 7-port entry-level USB hub, adaptor included

from **187,70 EUR**

Item no.: 385514
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

The UPort series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPort Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions. 7-port entry-level USB hub, adaptor included USB Interface- Speed 12 Mbps, 480 Mbps - USB Connector USB Type B- USB Standards USB 1.1/2.0 compliant- No. of USB Ports 7 Power Parameters- Input Voltage 12 to 40 VDC- Input Current 2.17 A @ 12 VDC Physical Characteristics- Housing Polycarbonate (PC)- Dimensions 80 x 35 x 185 mm (3.15 x 1.38 x [X6] in)- Weight Packaged: 890 g (1.96 lb) Product only: 875 g (1.93 lb) Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -20 to 75°C (-4 to 167°F) Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/m IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1 IEC 60068-2-3- Freefall IEC 60068-2-34 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 1,059,201 hrs- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

