

Item no.: 385270

CP-134EL-A-I W/O CABLE - Serial PCI Express x1 card with 4 RS-422485 connections

from **378,62 EUR**

Item no.: 385270
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's commitment to being a reliable serial connectivity provider is reflected in our long-term commitment to serial products and service availability. Our PCI Express, Universal PCI and PCI serial cards are designed for industrial applications and include models that operate reliably over a wide temperature range. 4-Port RS-422/485 Low-Profile PCI Express x1 Serial Card with Overvoltage Protection and Electrical Isolation Serial Interface- Comm. Controller 16C550C compatible- Bus PCI Express 1.0- Connector DB44 female- FIFO 128 bytes- Max. No. of Boards per PC 8- No. of Ports 4- Serial Standards RS-422 RS-485- Baudrate 50 bps to 921.6 kbps (supports non-standard baudrates)- Data Bits 5, 6, 7, 8- Stop Bits 1, 1.5, 2- Parity None Even Odd Space Mark- Flow Control None XON/XOFF- Isolation 2 kV- Surge 4 kV Serial Signals- RS-422 Tx+, Tx-, Rx+, Rx-, GND- RS-485-4w Tx+, Tx-, Rx+, Rx-, GND- RS-485-2w Data+, Data-, GND Serial Software Features- Windows Drivers Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10/11 (x86/x64), Windows 2008 R2/2012/2012 R2/2016/2019 (x64)/2022, Windows Embedded CE 5.0/6.0, Windows XP Embedded- Linux Drivers Linux kernel 5.x Linux kernel 4.x Linux kernel 3.x Linux kernel 2.6.x Linux kernel 2.4.x- UNIX Drivers Solaris 10 UnixWare 7 SCO OpenServer 5 SCO OpenServer 6- Arm®-based Platform Support Linux Kernel 5.x / 4.x Power Parameters- Input Current 3,414 mA @ 3.3 VDC Physical Characteristics- Dimensions 67.21 x 103 mm (2.65 x 4.06 in) LED Interface- LED Indicators Built-in Tx, Rx LEDs for each port Environmental Limits- Operating Temperature 0 to 55°C (32 to 131°F)- Storage Temperature (package included) -20 to 85°C (-4 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class B- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 4 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFMF Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 433,077 hrs- Standards Telcordia (Bellcore) Standard TR/SR

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

