

Item no.: 385329

CP-134U-I W/O CABLE - 4-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C

from **386,20 EUR**

Item no.: 385329
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

Moxa's dedication to being a trusted provider of serial connectivity is demonstrated by our long-term commitment to serial products and service availability. Our PCI Express, Universal PCI, and PCI serial boards are built for industrial applications, and include models that can operate reliably in a wide temperature range. 4-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature

Serial Interface Comm. Controller- MU860 (16C550C compatible) Bus- 32-bit Universal PCI Connector- DB44 female FIFO- 128 bytes Max. No. of Boards per PC- 8 No. of Ports- 4 Serial Standards- 2 x RS-232/422/485, 2 x RS-422/485 Baudrate- 50 bps to 921.6 kbps Data Bits- 5, 6, 7, 8 Stop Bits- 1, 1.5, 2 Parity- None, Even, Odd, Space, Mark Flow Control- None, RTS/CTS, XON/XOFF Isolation- 2 kV Serial Signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND RS-485-2w- Data+, Data-, GND

Serial Software Features Windows Drivers- DOS, Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2/2016/2019 (x64), Windows Embedded CE 5.0/6.0, Windows XP Embedded Linux Drivers- Linux kernel 2.4.x, Linux kernel 2.6.x, Linux kernel 3.x, Linux kernel 4.x, Linux kernel 5.x UNIX Drivers- QNX 6, SCO OpenServer, UnixWare 7, Solaris 10, FreeBSD Power Parameters Input Current- 850 mA @ 5 VDC Physical Characteristics Dimensions- 115 x 120 mm (4.52 x 4.72 in) LED Interface LED Indicators- Built-in Tx, Rx LEDs for each port Environmental Limits Operating Temperature- 0 to 55°C (32 to 131°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Standards and Certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class B EMS- IEC 61000-4-2 ESD- Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m Declaration Green Product- RoHS, CRoHS, WEEE MTBF Time- 480,209 hrs Standards- Telcordia SR332

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

