

Item no.: 375032

TL-SG3428XPP-M2 - JetStream Switch, 24x PoE, 500W

from **953,22 EUR**

Item no.: 375032
 shipping weight: 6.20 kg
 Manufacturer: TP-LINK



Product Description

The switch provides 24x 100/1000/2500 Mbps LAN ports for clients and additionally 4x optical SFP+ ports serving primarily as an uplink with a total switching capacity of 200 Gbps. All 24 ports support 802.3af/at (max 30W/port) PoE, 8 ports even 802.3bt (max 60W/port) PoE. The total PoE budget is 500W for all ports. For management and monitoring, it is possible to use the usual access via the web interface and protocols, for example. CLI, SNMP, RMO, but also centralized cloud management and software controller. Omada hardware controller (OC200/OC300) is also supported. Switch loaded with features The switch provides high-performance routing based on IP, MAC, TCP or UDP. All in combination with advanced security strategies (IP-MAC-Port Binding, ACL, Port Security, DoS Defend, Storm control, DHCP Snooping, 802.1X, Radius Authentication...). With all these advanced features, the gigabit L2+ JetStream switch is an ideal choice for small and medium-sized business network solutions. Omada Controller The Omada Software Defined Networking (SDN) platform integrates network devices, including Access Points, Switches, Gateway routers and provides 100% centralized management in the cloud. Omada creates a highly scalable network including control from a single interface. Provides seamless wireless and wired connectivity, ideal for use in hospitality, education, retail, offices and more. Package contents- Device- Power cord- Mounts for 19" rack Connectors and Interfaces- LAN speed:(24) 100M/1G/2.5G- Optical interfaces:(4) 10Gbps- Serial port:micro USB, RJ45 Power- Power type:Mains power (230V)- PoE type:PoE-Out (only)- PoE-Out standards:802.3af, 802.3at, 802.3bt- PoE Out ports:24- PoE budget [W]:500- Max. power consumption [W]:629- Power via connector/terminal:230V AC Physical characteristics- Design:Rackmount- Fans:(3) 40 x 40 mm- Chassis design:Metal- Operating temperature [°C]:0 up to 40- Width [mm]:440- Height [mm]:44- Depth [mm]:330 General- Switching capacity [Gbps]:200- MAC address table:32000- Jumbo frame [Bytes]:9000- Packet forwarding rate [Mpps]:148.8 Software- Web management:Yes- Management:Web management, SSH, Telnet, Omada controller- Features:VLAN, QoS, DHCP snooping- Default IP address:192.168.0.1- Default login and password:admin / admin

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

