

Item no.: 375062

## DECO P9(2-PACK) - - Mesh Wi-Fi system (2-pack)

## ₽ sp-link

## from 167,31 EUR

Item no.: 375062 shipping weight: 1.50 kg Manufacturer: TP-LINK

## Product Description

Powerline and wireless connections work together to transmit data between Deco units. The total network speed is greatly improved compared with using Wi-Fi only. Deco P9 combines dual-band Wi-Fi and powerline to establish a stronger mesh network. Powerline technology uses your home's electrical wiring to create stronger connections between Deco units, reducing the impact of walls and other obstacles on signal and providing even faster network speeds and truly seamless coverage. Deco P9 is compatible with other Deco models to form Mesh network. Expand Mesh Wi-Fi coverage anytime by simply adding more Decos. Simple, intuitive parental controls make it easy to keep your children safe while they're online. SpecificationHardware- Ports: 2 WAN/LAN Gigabit Ethernet Ports, 1 Power Port - Buttons: 1 Reset button on the underside- Antenna Type: 2 internal dual-band antennas per Deco unit - Dimensions: 7.5 x 3.6 x 3.6 in. (190.5 x 90.7 x 90.7 mm)- Power Input: 100-240V - 50/60Hz 0.5AWireless- Wireless Standards: IEEE 802.11 ac//n/a 5 GHz, 300 Mbps at 2.4 GHz - Transmit Power: FCC: <30 dBm, CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz) - Wireless Security: WPA-PSKKOftware- Working Mode: Router, Access Point- WAN Type: Dynamic IP/Static IP/PPPoE/L2TP/PPT- DHCP: Server, Client- Quality of Service; WMM- Firewall Security: SPI Firewall- Protocols: Supports IPv4 and IPv6- Guest Network: 2.4 GHz guest network x 1, 5 GHz guest network x 1- Features: Parental Controls, QoS (Quality of Service), Reporting, Assisted Setup, Address Reservation, Port Forwarding, TP-Link DDNS, VLAN, IPv6, LED Control- Management, Local Management, Remote ManagementPowerline- Powerline Rate: 1000Mbps- Standard: HomePlug AV2- Range: 300 meters / 1000 feet over electrical circuitOthers- CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC, RoHS- Smartphone/Tablet Requirements: iOS 9.0 or later, Android 4.4 or later- Environment: Operating Temperature: °0°C~40°C (32°F~104°F) Storage Temperature: ~40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing

**Specifications** 

Scan this QR code to view the product All details, up-to-date prices and availability

