

Item no.: 375051

DECO X50-DSL(1-PACK) - Mesh Wi-Fi 6 system



from **138,58 EUR**

Item no.: 375051
shipping weight: 1,30 kg
Manufacturer: TP-LINK

Product Description

Deco X50-DSL is the easiest way to guarantee a strong Wi-Fi signal in every corner of your home and at the same time connect your network to the Internet using a DSL line or classic Gigabit Ethernet. Wireless connectivity and optional linking of units either wired or wireless provide even higher network speed and truly seamless coverage. Want more coverage? Just add another Deco unit. Deco X20-DSL key features- Dual Band: 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)- VDSL2, ADSL, ADSL2, ADSL2+ support- Support 802.11a/b/g/n/ac/ax (Wi-Fi 6), 2x2 MU-MIMO- DSL Router, AP Router and Access Point operating modes- Support WPA3 encryption- (4) 10/100/1000 Mbps LAN (LAN/WAN) + RJ12 (DSL)- IPv6 support Hassle-free roaming with one Wi-Fi name TP-Link Mesh means that Deco units work together to create one unified network. Your phone or tablet automatically connects to the fastest Deco unit as you move around the house, creating a truly seamless Wi-Fi experience. Compatibility and easy extensibility All Deco units are compatible with each other. If you use more than one type of drive, use the best one as the main one (closest to the Internet). If you need to expand your network, simply purchase another Deco unit and adopt it into your existing network via the app. Package contents- Device- Power adapter- Patch cable Hardware- Ethernet Port: 4 x Gigabit ports per Deco unit (WAN/LAN auto-sensing)- Button: 1 RESET button above the ports- DSL Port: 1 RJ11 port- Antenna: 2 x dual-band antennas- Power Consumption (with power adapter): : 19.7 W max - Dimensions (W x D x H): 4.13 x 4.13 x 6.57 in (105 x 105 x 167 mm)- Compatibility: VDSL2/ADSL2+/ADSL2/ADSL - Power Adapter Input: 100-240 V~50/60 Hz 0.6 A- Power Adapter Output: 12 V 1.5 A Wireless - Wireless Standards: IEEE 802.11a/n/ac/ax 5 GHz, IEEE 802.11b/g/n/ax 2.4 GHz- Mesh protocol: 802.11k/v/r- Frequency: 2.4 GHz and 5 GHz- Signal Rate: 2402 Mbps on 5 GHz + 574 Mbps on 2.4 GHz+ Transmit Power: CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz)- Wireless Security: WPA/WPA2/WPA3 Software- Working Mode: DSL, Router, Access Point- WAN Type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP- DHCP: Server- Protocols: Supports IPv4 and IPv6- Guest Network: 2.4 GHz Guest Network x1, 5 GHz Guest Network x1- Features: TP-Link HomeShield, AI-Driven Mesh, BSS Color, OFDMA, 1024-QAM, MU-MIMO, Optional Ethernet Backhaul, Assisted Setup, Address Reservation, Port Forwarding, TP-Link DDNS, IPTV, IPv6, Firewall Rules, LED Control- Management: Local Management; Remote Management; Multi-Managers Others- Certification: CE, RoHS- Environment: Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~60°C (-40°F~140°F) Operating Humidity: 10%~90% RH Storage Humidity: 5%~90% RH

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

