

Item no.: 332488

MX-EX2028PXA-E - Intelligent Ethernte PoE Switch 24 x 1G, 4x SFP+, no power cord

from 949,20 EUR

shipping weight: 3.60 kg
Manufacturer: Cambium Networks



Product Description

Intelligent Ethernet PoE Switch 24 x 1G and 4 SFP+ fiber ports no power cord

Cambium Networks next generation switching platform offers a cloud supported, high performance, feature rich ethernet switching solution. The cnMatrix(TM) platform of switches provides:

- Energy efficient gigabit
- Layer 3 (OSPF and RIP)
 Flexible Power over Ethernet (PoE) options
- Multiple port density options

The cnMatrix series of fully managed switches delivers full Layer2 capabilities with enhanced access security. Switches deliver power savings with several models offering fanless operation. The cnMatrix switch series offers flexibility with 4 – 10 Gbps (SFP+) uplinks on the 28 port models while offering 2 - 1Gbps (SFP) uplink ports on the 10 port models. Features

- Throughput: 128 Gbps
- Non-Blocking: yes
- Non-Blocking: yes
 PoE enabled ports: 24
 PoE power budget: 400
 10/100/1000 ports: 24
 Uplink ports: 4 SFP+
 Serial console: yes

- USB: yesOOB port: yes
- Rack mount kit: yesInternal fans: 2

Specifications

- Switching capacity: 128 Gbps
 10/100/1000 Mbps ports: 24
 Number of uplink ports: (4) SFP+
 PoE enabled ports: 24
 PoE power budget: 400W
 Base IPv4 (static): 64
 Maximum MAC addresses: 16384
 Maximum ARP entries: 512
 Max VLANs: 4094
 Maximum MSTPs: 8
 Maximum routes (Static): 64

- Max VLAN: 4094
 Maximum MSTPs: 8
 Maximum MSTPs: 8
 Maximum MSTPs: 8
 Dynamic routing: 512
 LACP/trunking: 8 LAGs/8 links per 92166
 QoS priority queues: 8
 Maximum IGMP multicast groups: 256
 Max PVRST: 32
 Lüfter: 2
 Cambium Auto Edge: Yes
 MTBF (hours): 432,283.26
 Cambium Auto Edge: Yes
 MTBF (hours): 432,283.26
 Power budget: n/a
 Power budget: n/a
 Power supply: AC/Internal AC
 Weight: 8 lbs 12oz
 Dimensions: 440 x 44 x 209 mm
 LEDs per port: Connection/Activity PoE
 Temperature ranges 0 °C 50 °C
 Operating humidity: +55 °C at 95% RH
 Storage temperature: -40 °C ~ 70 °C

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

