

Item no.: 384599

CSM-400-1225-T - 10100BaseT(X) to 100BaseFX plug-in management module converter, WDM-B single-mo

from **373,23 EUR**

Item no.: 384599
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

10/100BaseT(X) to 100BaseFX plug-in management module converter, WDM-B single-mode SC connection, -40 to 75°C operating temperature Ethernet interface- 10/100BaseT(X) ports (RJ45 connection): 1- 100BaseFX ports, WDM-B single-mode SC connection: 1- Magnetic isolation protection: 1.5 kV (built-in)- Standards: IEEE 802.3u for 100BaseT(X) and 100BaseFX Security functions- Authentication: Local database (password only)- Encryption: HTTPS; AES-128; RSA-1024; SHA-1; SHA-256- Security protocols: SSHv2; HTTPS (TLS 1.2) Performance parameters- Input current: 220 mA @ 12 VDC- Input voltage: 12 VDC- Overload current protection: Supported- Power consumption: 220 mA @ 12 VDC Physical characteristics- Dimensions: 86.8 x 124.3 x 21 mm (3.42 x 4.89 x 0.83 in.)- Weight: Product only: 125 g (0.28 lb) Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- EMC: EN 55032/35- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV(AC), 1 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFM IEC 61000-4-11- Environmental testing: IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-3- Safety: EN 62368-1; UL 62368-1- Vibration: IEC 60068-2-6 MTBF- Time: 1,454,560 hours- Standards: Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

