

Item no.: 387846

EDS-308-MM-SC-T - Unmanaged Ethernet switch with 6 10/100BaseT(X) ports

from **436,18 EUR**

Item no.: 387846
shipping weight: 0.80 kg
Manufacturer: MOXA



Product Description

Moxa has a large portfolio of industrial unmanaged switches that have been specially developed for industrial Ethernet infrastructures. Our unmanaged Ethernet switches fulfil the strict standards required for operational reliability in harsh environments. Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multimode ports with SC connectors, relay output warning, Operating temperature from -40 to 75 °C Input/output interface Alarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDC Ethernet interface 10/100BaseT(X) ports (RJ45 connection) ports (RJ45 connection)- 6- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection 100BaseFX ports (multi-mode SC connection)- 2 standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control Fibre optic DIP switch configuration Ethernet interface- Port break alarm Switch characteristics MAC table size- 2 kbits Packet buffer size- 768 K Processing type- Store and Forward Power parameters Input current- 0.15 A @ 24 VDC Connection- 1 removable 6-contact terminal block(s) Operating voltage- 9.6 to 60 VDC Input voltage- Redundant dual inputs- 12/24/48 VDC Reverse polarity protection- Supports Overload current protection- Supports Physical properties Housing- Metall IP protection class- IP30 Dimensions- 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in) Weight- 790 g (1.75 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Ambient conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 85°C) -40 to 85°C (-40 to 185°F) Ambient relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- UL 60950-1- CSA C22.2 No. 60950-1- EN 62368 (LVD) EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 MHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V Hazardous areas- ATEX- Class I Division 2 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-32 Maritime- DNVMTB Time- 2,382,553 hours Standards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

