

Item no.: 387320

USW-PRO-MAX-16-POE - USW-PRO-MAX-16-POE-EU - USW-Pro-Max-16-PoE

from **423,25 EUR**

Item no.: 387320
 shipping weight: 2.10 kg
 Manufacturer: Ubiquiti



Product Description

A 16-port Layer 3 Etherlighting™ switch with 2.5GbE, PoE++ output and versatile mounting options. Etherlighting™ ports illuminated to show port position, speed/link and native VLAN/network*(4) 2.5 GbE PoE++ ports(12) GbE PoE+ ports(2) 10G SFP+ ports180W total PoE availabilityVersatile desktop, wall and rack** mountingSilent, fanless cooling systemTechnical specificationsDimensions325.1 x 160 x 43.7 mm (12.8 x 6.3 x 1.7")Weight2.1 kg (4.6 lb)Housing materialSGCC steelHardwareManagement interfaceEthernetIn-Band- Network interface(12) GbE RJ45 ports(4) 1/2.5 GbE RJ45 ports(2) 10G SFP+ ports- PoE interface(12) PoE/PoE+ (Pins 1, 2+; 3, 6-)(4) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)- Total non-blocking throughput42Gbps- Switching capacity84Gbps- Forwarding rate62.496 Mpps-Power supply methodDC adapter- Power supply54V, 210W- Maximum power consumption30W(without PoE output)- Total available PoE180W- Max. PoE power per port through PSE- PoE: 15.4 W- PoE+: 30 W- PoE++: 60 W- Voltage range PoE mode- PoE: 44-57 V- PoE+/PoE++: 50-57 V- LCM display(1) 1.3" touchscreen- Factory reset button- Operating ambient temperature-5 to 40° C (23 to 104° F)- Operating humidity10 to 90% non-condensing- CertificationsCE, FCC, ICSwitching functionsLayer 2 functions- GMP snooping- STP / RSTP with prioritisation and deactivation at port level- Port isolation- Storm control- Voice VLAN- Port mirroring- LACP port aggregation- Multicast / broadcast rate limiting- MAC address blocking- Flow control- 802.1X control- Jumbo frames- Proprietary loop protection- DHCP snooping / guarding- Egress rate limiting- LLDP-MED- Port restriction by MAC- Device isolation with ACLsLayer 3 functions- DHCP for locally managed networks- DHCP relay- Inter-VLAN routing between networks on the same switch- Static routing between local networks - DHCP for locally managed networks - DHCP relay Static routing between local networks- Network Isolation with ACLsEtherlighting™- Ethernet- Localisation- Speed/Link- Native VLAN/Network-SFP+- Localisation- Speed/Link- Native VLAN/NetworkApplication RequirementsUniFi NetworkVersion8.1.127 and higher

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

