


Item no.: 390882

U6-MESH-PRO-EU - U6-Mesh-Pro Weatherproof pole- and wall-mountable WiFi 6 access point with a hig

from **201,11 EUR**

Item no.: 390882
shipping weight: 0.80 kg
Manufacturer: Ubiquiti



Product Description

Mechanical- Dimensions: 343.2 x 181.2 x 60.2 mm (13.5 x 7.1 x 2.4")- Weight: 819 g (1.8 lb)- Enclosure material: UV-stabilized polycarbonate- Mount material: Aluminum alloy, steel- Pole mount diameter: 1~2.5" on pipe outer diameter- Weatherproofing: IPX6Hardware- Networking interface: (2) GbE RJ45 ports- Management interface: Ethernet, WiFi- Power method: PoE- Power supply: UniFi PoE switch, 48V, 0.5A PoE adapter (Included)- Supported voltage range: 42.5—57V DC- Max. power consumption: 9WMax. TX power- 2.4 GHz: 22 dBm- 5 GHz: 27 dBm- 6 GHz: --MIMO- 2.4 GHz: 2 x 2 (DL/UL MU MIMO)- 5 GHz: 2 x 2 (DL/UL MU-MIMO)- 6 GHz: --Throughput rate- 2.4 GHz: 573.5 Mbps- 5 GHz: 2.4 Gbps- 6 GHz: --Antenna gain- 2.4 GHz: 8 dBi- 5 GHz: 8 dBi- 6 GHz: -- LEDs: White/blue- Button: Factory reset- Mounting: Wall, pole (Included)- Ambient operating temperature: -30 to 60° C (-22 to 140° F)- Ambient operating humidity: 5 to 95% noncondensing- Certifications: CE, FCC, ICSoftware- WiFi standards: 802.11a/b/g/n/ac/ax- Wireless security: WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)- BSSID: 8 per radio- VLAN: 802.1Q- Advanced: QoS Per-user rate limiting- Guest traffic isolation: Supported- Concurrent clients: 350+Supported Data Rates- 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps- 802.11b: 1, 2, 5.5, 11 Mbps- 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps- 802.11n: (WiFi 4) 6.5 Mbps to 300 Mbps (MCS0 - MCS15 , HT 20/40)- 802.11ac: (WiFi 5) 6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160)- 802.11ax: (WiFi 6) 7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)Application Requirements- UniFi Network: Version 8.1.127 and later

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

