

Item no.: 390884

## U7-PRO-MAX - Ceiling-mount tri-band WiFi 7 AP with a dedicated scanning radio and

from **279,51 EUR**

Item no.: 390884  
shipping weight: 0.70 kg  
Manufacturer: Ubiquiti



### Product Description

Mechanical- Dimensions: Ø206 x 46 mm (Ø8.1 x 1.8")- Weight: 680 g (1.5 lb)- Enclosure material: Polycarbonate, aluminum- Mount material: Stainless steel (SUS304), galvanized steel (SGCC)Hardware- Networking interface: (1) 1/2.5 GbE RJ45 port- Management interface: Ethernet - Power method: PoE+- Power supply: UniFi PoE switch- Supported voltage range: 44—57V DC- Max. power consumption: 22WMax. TX power- 2.4 GHz: 23 dBm- 5 GHz: 29 dBm- 6 GHz: 23 dBmMIMO- 2.4 GHz: 2 x 2- 5 GHz: 4 x 4- 6 GHz: 2 x 2Throughput rate- 2.4 GHz: 688 Mbps- 5 GHz: 8648 Mbps- 6 GHz: 5765 MbpsAntenna gain- 2.4 GHz: 4 dBi- 5 GHz: 6 dBi- 6 GHz: 5.9 dBi- LEDs: White/blue- Button: Factory reset- Mounting: Wall, ceiling (Included)- Ambient operating temperature: -30 to 60° C (-22 to 140° F)- Ambient operating humidity: 5 to 95% noncondensing- Certifications: CE, FCC, ICSoftware- WiFi standards: 802.11a/b/g/n/ac/ax/be- Wireless security: WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3/PPSK)- BSSID: 8 per radio- VLAN: 802.1Q- Advanced QoS: Per-user rate limiting- Guest traffic isolation: Supported- Concurrent clients: 500+Supported Data Rates- 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps- 802.11b: 1, 2, 5.5, 11 Mbps- 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps- 802.11n: 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)- 802.11ac: (WiFi 5) 6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160)- 802.11ax: (WiFi 6/6E) 7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)802.11be (WiFi 7)- 5 GHz: 7.3 Mbps to 8.6 Gbps (MCS0 - MCS13 NSS1/2/3/4, EHT 20/40/80/160/240)- 6 GHz: 7.3 Mbps to 5.7 Gbps (MCS0 - MCS13 NSS1/2, EHT 20/40/80/160/240/320)Application Requirements- UniFi Network: Version 8.2.93 and later

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

