

Item no.: 387763

SFP-2.5GMLC-T - SFP module with 1 2.5GBaseFX port with LC connection, multimode

from **243,51 EUR**

Item no.: 387763
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa's small form-factor pluggable transceiver (SFP) Ethernet fibre optic modules for 2.5 Gigabit Ethernet provide coverage over a wide range of communication distances. SFP module with 1 2.5GBaseFX port with LC connector, multimode, for 170, 200, 550, 600 m transmission, -40 to 85 °C operating temperature Ethernet interface Connector- Duplex LC connector Fibre optic- Typical distance: To achieve the typical distance of the specified fibre optic transceiver, please observe the formula: Link budget(dB) > Scattering loss(dB) + Total loss(dB) Performance parameters Power consumption- Max. 1 W Ambient conditions Operating temperature- -40 to 85°C (-40 to 185°F) Storage temperature (in packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- IEC 60825-1- UL 62368-1- IEC 62368-1 EMC- EN 55032/35 EMI- FCC 15B Test Report- ICES-003: 2020 Edition 7 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV/2 kV(AC), 0.5 kV(DC); Signal: 1 kV- IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1 V- IEC 61000-4-8 PFMF: 1 A/m at 50 Hz- IEC 61000-4-11: Voltage dips and interruptions

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

