

Item no.: 384799

UVC-G5-DOME-3 - Next-generation 2K HD PoE ceiling camera with improved dynamic range

from **574,88 EUR**

Item no.: 384799
shipping weight: 0.40 kg
Manufacturer: Ubiquiti



Product Description

Mechanical- Dimensions: Ø109.2 x 64.5 mm (Ø4.3 x 2.5")- Weight Without bracket: 370 g (13.1 oz)- With bracket: 390 g (13.8 oz)- Housing material: aluminium alloy, polycarbonate, hard-coated dome- Mounting material: polycarbonate, stainless steel- Weather resistance: IPX4- Resistance: IK08Optics- Sensor: 5MP CMOS- Lens: Fixed focal length- Viewing angle: H: 102.4°, V: 54.9°, D: 120.6°- Night mode: Built-in IR LED illumination and IR cut filterVideo- Resolution 4MP 2688 x 1512 (16:9)- Max. Frame rate 30 FPS- Image settings colour, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlaySystem- Processor: Dual-Core Arm® Cortex®-A7 based chip- Network interface: 10/100 MbE RJ45 connection- Max. Power consumption 5W- Power supply method PoE- Supported voltage range 37-57V DC- LED R/G/B/W- Factory reset button- Wall mounting, Ceiling mount- Ambient temperature -20 to 40° C (-4 to 104° F)- Ambient humidity 0 to 90% non-condensing- Certifications FCC, IC, CEAudio- Microphone Yes (can be disabled)- Speaker YesSoftware- Web application UniFi Protect: Version 2.2.7 or 2.7.28 and higher- Mobile App: UniFi Protect iOS™ and Android™: Version 1.10.0 and higher

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

