

Item no.: 385524

**AWK-3131A-M12-RCC-EU - 802.11n railway onboard indoor single radio access pointclient, EU band, IP30, -**

**from 1.322,09 EUR**

Item no.: 385524  
shipping weight: 1.00 kg  
Manufacturer: MOXA



 [Product Description](#)

---

802.11n railway onboard indoor single radio access point/client, EU band, IP30, -25 to 60°C operating temperature  
WLAN Interface  
WLAN Standards: 802.11a/b/g/n; 802.11i  
Wireless Security: Modulation Type: DSSS OFDM  
802.11b: CCK @ 11/5.5 Mbps  
802.11b: DQPSK @ 2 Mbps  
802.11b: DBPSK @ 1 Mbps  
802.11a/g: 64QAM @ 54/58 Mbps  
802.11a/g: 16QAM @ 36/24 Mbps  
802.11a/g: QPSK @ 18/12 Mbps  
802.11a/g: BPSK @ 9/6 Mbps  
802.11n: 64QAM @ 300 Mbps to BPSK @ 6.5 Mbps  
Frequency Band for EU (20 MHz operating channels): 2.412 to 2.472 GHz (13 channels)  
5.180 to 5.240 GHz (4 channels)  
5.260 to 5.320 GHz (4 channels)  
5.500 to 5.700 GHz (11 channels)  
Wireless Security: SSID broadcast enable/disable  
WEP encryption (64-bit and 128-bit)  
WPA/WPA2-Personal  
WPA/WPA2-Enterprise (IEEE 802.1X/RADIUS, TKIP, AES)  
Transmission Rate: 802.11b: 1 to 11 Mbps  
802.11a/g: 6 to 54 Mbps  
802.11n: 6.5 to 300 Mbps  
Transmitter Power for 802.11a: 23±1.5 dBm @ 6 to 24 Mbps  
21±1.5 dBm @ 36 Mbps  
20±1.5 dBm @ 48 Mbps  
18±1.5 dBm @ 54 Mbps  
Transmitter Power for 802.11n (5 GHz): 23±1.5 dBm @ MCS0 20 MHz  
20±1.5 dBm @ MCS1 20 MHz  
20±1.5 dBm @ MCS2 20 MHz  
20±1.5 dBm @ MCS3 20 MHz  
19±1.5 dBm @ MCS4 20 MHz  
18±1.5 dBm @ MCS5 20 MHz  
18±1.5 dBm @ MCS6 20 MHz  
18±1.5 dBm @ MCS7 20 MHz  
23±1.5 dBm @ MCS8 20 MHz  
20±1.5 dBm @ MCS9 20 MHz  
20±1.5 dBm @ MCS10 20 MHz  
19±1.5 dBm @ MCS11 20 MHz  
19±1.5 dBm @ MCS12 20 MHz  
19±1.5 dBm @ MCS13 20 MHz  
18±1.5 dBm @ MCS14 20 MHz  
18±1.5 dBm @ MCS15 40 MHz  
Transmitter Power for 802.11b: 26±1.5 dBm @ 1 Mbps  
26±1.5 dBm @ 2 Mbps  
26±1.5 dBm @ 5.5 Mbps  
25±1.5 dBm @ 11 Mbps  
Transmitter Power for 802.11g: 23±1.5 dBm @ 6 to 24 Mbps  
21±1.5 dBm @ 36 Mbps  
19±1.5 dBm @ 48 Mbps  
18±1.5 dBm @ MCS11 20 MHz  
19±1.5 dBm @ MCS12 20 MHz  
19±1.5 dBm @ MCS13 20 MHz  
18±1.5 dBm @ MCS14 20 MHz  
18±1.5 dBm @ MCS15 20 MHz  
23±1.5 dBm @ MCS0 20 MHz  
20±1.5 dBm @ MCS1 20 MHz  
20±1.5 dBm @ MCS2 20 MHz  
20±1.5 dBm @ MCS3 20 MHz  
19±1.5 dBm @ MCS4 20 MHz  
19±1.5 dBm @ MCS5 20 MHz  
18±1.5 dBm @ MCS6 20 MHz  
18±1.5 dBm @ MCS7 20 MHz  
23±1.5 dBm @ MCS8 20 MHz  
20±1.5 dBm @ MCS9 20 MHz  
20±1.5 dBm @ MCS10 20 MHz  
19±1.5 dBm @ MCS11 20 MHz  
19±1.5 dBm @ MCS12 20 MHz  
19±1.5 dBm @ MCS13 20 MHz  
18±1.5 dBm @ MCS14 20 MHz  
18±1.5 dBm @ MCS15 40 MHz  
Receiver Sensitivity for 802.11a (measured at 5.680 GHz): Typ. -90 @ 6 Mbps  
Typ. -88 @ 9 Mbps  
Typ. -88 @ 12 Mbps  
Typ. -85 @ 18 Mbps  
Typ. -81 @ 24 Mbps  
Typ. -78 @ 36 Mbps  
Typ. -74 @ 48 Mbps  
Typ. -74 @ 54 Mbps  
Receiver Sensitivity for 802.11n (5 GHz): measured at 5.680 GHz: Typ. -88 dBm @ MCS0 20 MHz  
Typ. -85 dBm @ MCS1 20 MHz  
Typ. -82 dBm @ MCS2 20 MHz  
Typ. -79 dBm @ MCS3 20 MHz  
Typ. -76 dBm @ MCS4 20 MHz  
Typ. -71 dBm @ MCS5 20 MHz  
Typ. -70 dBm @ MCS6 20 MHz  
Typ. -69 dBm @ MCS7 20 MHz  
Typ. -95 dBm @ MCS8 20 MHz  
Typ. -91 dBm @ MCS9 20 MHz  
Typ. -87 dBm @ MCS10 20 MHz  
Typ. -80 dBm @ MCS11 20 MHz  
Typ. -78 dBm @ MCS12 20 MHz  
Typ. -74 dBm @ MCS13 20 MHz  
Typ. -71 dBm @ MCS14 20 MHz  
Typ. -84 dBm @ MCS15 20 MHz  
Receiver Sensitivity for 802.11b (measured at 2.437 GHz): Typ. -93 dBm @ 1 Mbps  
Typ. -93 dBm @ 2 Mbps  
Typ. -93 dBm @ 5.5 Mbps  
Typ. -88 dBm @ 11 Mbps  
Receiver Sensitivity for 802.11g (measured at 2.437 GHz): Typ. -88 dBm @ 6 Mbps  
Typ. -86 dBm @ 9 Mbps  
Typ. -85 dBm @ 12 Mbps  
Typ. -85 dBm @ 18 Mbps  
Typ. -85 dBm @ 24 Mbps  
Typ. -82 dBm @ 36 Mbps  
Typ. -78 dBm @ 48 Mbps  
Typ. -74 dBm @ 54 Mbps  
Receiver Sensitivity for 802.11n (2.4 GHz; measured at 2.437 GHz): Typ. -89 dBm @ MCS0 20 MHz  
Typ. -85 dBm @ MCS1 20 MHz  
Typ. -85 dBm @ MCS2 20 MHz  
Typ. -82 dBm @ MCS3 20 MHz  
Typ. -78 dBm @ MCS4 20 MHz  
Typ. -74 dBm @ MCS5 20 MHz  
Typ. -72 dBm @ MCS6 20 MHz  
Typ. -70 dBm @ MCS7 20 MHz  
Typ. -95 dBm @ MCS8 20 MHz  
Typ. -90 dBm @ MCS9 20 MHz  
Typ. -87 dBm @ MCS10 20 MHz  
Typ. -83 dBm @ MCS11 20 MHz  
Typ. -80 dBm @ MCS12 20 MHz  
Typ. -74 dBm @ MCS13 20 MHz  
Typ. -71 dBm @ MCS14 20 MHz  
Typ. -83 dBm @ MCS15 20 MHz  
Typ. -69 dBm @ MCS0 40 MHz  
Typ. -83 dBm @ MCS1 40 MHz  
Typ. -83 dBm @ MCS2 40 MHz  
Typ. -80 dBm @ MCS3 40 MHz  
Typ. -76 dBm @ MCS4 40 MHz  
Typ. -73 dBm @ MCS5 40 MHz  
Typ. -69 dBm @ MCS6 40 MHz  
Typ. -67 dBm @ MCS7 40 MHz  
Typ. -93 dBm @ MCS8 40 MHz  
Typ. -88 dBm @ MCS9 40 MHz  
Typ. -85 dBm @ MCS10 40 MHz  
Typ. -82 dBm @ MCS11 40 MHz  
Typ. -78 dBm @ MCS12 40 MHz  
Typ. -73 dBm @ MCS13 40 MHz  
Typ. -69 dBm @ MCS14 40 MHz  
Typ. -67 dBm @ MCS15 40 MHz  
WLAN Operation Mode: Access point, Client, Client-Router, Sniffer  
Antenna Connectors: QMA Ethernet Interface  
PoE Ports (10/100/1000BaseT(X), M12 A-coded 8-pin female connector): 1 Standards: IEEE 802.3 for 10BaseT  
IEEE 802.3u for 100BaseT(X)  
IEEE 802.3ab for 1000BaseT  
IEEE 802.3af for PoE  
IEEE 802.1Q for VLAN Tagging  
10/100/1000BaseT(X) Ports (M12 A-coded 8-pin female connector): 1, M12 A-coded 8-pin female connector, 10/100/1000BaseT(X) auto negotiation speed, F/H duplex mode, auto MDI/MDI-X connection  
Ethernet Software Features Management: General: Proxy ARP, DNS, HTTP, HTTPS, IP, ICMP, SNMP, TCP, UDP, RADIUS, SNMP, DHCPAP-only: ARP, BOOTP, DHCP  
Security: RADIUS Firewall Filter: MAC/IP Protocol/Port-based  
Serial Interface Console Port: RS-232 (RJ45-type)  
LED Interface  
LED Indicators: PWR1, PWR2, PoE, FAULT, STATE, SIGNAL, Client, WLAN, LAN  
Input/Output Interface Digital Inputs: 2+13 to +30 V for state 1+3 to -30 V for state 0  
Max. input current: 8 mA  
Alarm Contact Channels: Relay output with current carrying capacity of 1 A @ 24 VDC  
Buttons: Reset button  
Physical Characteristics Housing: Metall  
IP Rating: IP30  
Dimensions: 52.9 x 151.9 x 127.4 mm (2.08 x 5.98 x 5.02 in)  
Weight: 850 g (1.87 lb)  
Installation: DIN-rail mounting, Wall mounting (with optional kit)  
Power Parameters Input Current: 0.67 A @ 12 VDC, 0.17 A @ 48 VDC  
Input Voltage: 12 to 48 VDC, Redundant dual inputs, 48 VDC Power-over-Ethernet  
Power Connector: 1 removable 10-contact terminal block(s)  
Power Consumption: Maximum 8.03 W  
Reverse Polarity Protection: Supported  
Environmental Limits Operating Temperature: Standard Models: -25 to 60°C (-13 to 140°F)  
Storage Temperature (package included): -40 to 85°C (-40 to 185°F)  
Ambient Relative Humidity: 5 to 95% (non-condensing)  
Standards and Certifications EMC: EN 55032/24  
EMI: CISPR 32, FCC Part 15B Class B  
EMS: IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV  
IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m  
IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV  
IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV  
IEC 61000-4-6 CS: 10 V  
IEC 61000-4-8 PFM  
Railway: EN 50155, EN 50121-4  
Railway Fire Protection: EN 45545-2  
Radio: EN 300 328, EN 301 893, MIC, FCC ID SLE-WAPN008, IDA Safety: UL 60950-1, IEC 60950-1, EN 60950-1 (LVD)  
MTBF Time: 742,649 hrs  
Standards: Telcordia SR332

## Specifications

Scan this QR code to view the product  
All details, up-to-date prices and availability

