

Item no.: 385470

AWK-3131A-M12-RTG-EU-T - 802.11n railway onboard indoor single radio access pointclient, M12, EU band, IP

from 1.256,31 EUR

Item no.: 385470
shipping weight: 1.00 kg
Manufacturer: MOXA



 [Product Description](#)

802.11n railway onboard indoor single radio access point/client, M12, EU band, IP30, -40 to 75°C operating temperature WLAN Interface WLAN Standards: 802.11a/b/g/n; 802.11i Wireless Security Modulation Type: DSSS OFDM 802.11b: CCK @ 11/5.5 Mbps 802.11b: DQPSK @ 2 Mbps 802.11b: DBPSK @ 1 Mbps 802.11a/g: 64QAM @ 54/48 Mbps 802.11a/g: 16QAM @ 36/24 Mbps 802.11a/g: QPSK @ 18/12 Mbps 802.11a/g: BPSK @ 9/6 Mbps 802.11n: 64QAM @ 300 Mbps to BPSK @ 6.5 Mbps Frequency Band for EU (20 MHz operating channels): 2.412 to 2.472 GHz (13 channels) 5.180 to 5.240 GHz (4 channels) 5.260 to 5.320 GHz (4 channels) 5.500 to 5.700 GHz (11 channels) Wireless Security: SSID broadcast enable/disable WEP encryption (64-bit and 128-bit) WPA/WPA2-Personal WPA/WPA2-Enterprise (IEEE 802.1X/RADIUS, TKIP, AES) Transmission Rate: 802.11b: 1 to 11 Mbps 802.11a/g: 6 to 54 Mbps 802.11n: 6.5 to 300 Mbps Transmitter Power for 802.11a: 23±1.5 dBm @ 6 to 24 Mbps 21±1.5 dBm @ 36 Mbps 20±1.5 dBm @ 48 Mbps 18±1.5 dBm @ 54 Mbps Transmitter Power for 802.11n (5 GHz): 23±1.5 dBm @ MCS0 20 MHz 20±1.5 dBm @ MCS1 20 MHz 20±1.5 dBm @ MCS2 20 MHz 20±1.5 dBm @ MCS3 20 MHz 19±1.5 dBm @ MCS4 20 MHz 18±1.5 dBm @ MCS5 20 MHz 18±1.5 dBm @ MCS6 20 MHz 18±1.5 dBm @ MCS7 20 MHz 23±1.5 dBm @ MCS8 20 MHz 20±1.5 dBm @ MCS9 20 MHz 20±1.5 dBm @ MCS10 20 MHz 20±1.5 dBm @ MCS11 20 MHz 19±1.5 dBm @ MCS12 20 MHz 19±1.5 dBm @ MCS13 20 MHz 18±1.5 dBm @ MCS14 20 MHz 18±1.5 dBm @ MCS15 20 MHz 23±1.5 dBm @ MCS0 40 MHz 20±1.5 dBm @ MCS1 40 MHz 20±1.5 dBm @ MCS2 40 MHz 20±1.5 dBm @ MCS3 40 MHz 19±1.5 dBm @ MCS4 40 MHz 18±1.5 dBm @ MCS5 40 MHz 17±1.5 dBm @ MCS6 40 MHz 17±1.5 dBm @ MCS7 40 MHz 17±1.5 dBm @ MCS8 40 MHz 17±1.5 dBm @ MCS9 40 MHz 17±1.5 dBm @ MCS10 40 MHz 17±1.5 dBm @ MCS11 40 MHz 19±1.5 dBm @ MCS12 40 MHz 19±1.5 dBm @ MCS13 40 MHz 18±1.5 dBm @ MCS14 40 MHz 18±1.5 dBm @ MCS15 40 MHz Transmitter Power for 802.11b: 26±1.5 dBm @ 1 Mbps 26±1.5 dBm @ 2 Mbps 26±1.5 dBm @ 5.5 Mbps 25±1.5 dBm @ 11 Mbps Transmitter Power for 802.11g: 23±1.5 dBm @ 6 to 24 Mbps 21±1.5 dBm @ 36 Mbps 19±1.5 dBm @ 48 Mbps 19±1.5 dBm @ MCS0 20 MHz 21±1.5 dBm @ MCS1 20 MHz 21±1.5 dBm @ MCS2 20 MHz 21±1.5 dBm @ MCS3 20 MHz 20±1.5 dBm @ MCS4 20 MHz 19±1.5 dBm @ MCS5 20 MHz 18±1.5 dBm @ MCS6 20 MHz 18±1.5 dBm @ MCS7 20 MHz 23±1.5 dBm @ MCS8 20 MHz 20±1.5 dBm @ MCS9 20 MHz 20±1.5 dBm @ MCS10 20 MHz 20±1.5 dBm @ MCS11 20 MHz 20±1.5 dBm @ MCS12 20 MHz 19±1.5 dBm @ MCS13 20 MHz 18±1.5 dBm @ MCS14 20 MHz 18±1.5 dBm @ MCS15 20 MHz 23±1.5 dBm @ MCS0 40 MHz 20±1.5 dBm @ MCS1 40 MHz 20±1.5 dBm @ MCS2 40 MHz 20±1.5 dBm @ MCS3 40 MHz 19±1.5 dBm @ MCS4 40 MHz 18±1.5 dBm @ MCS5 40 MHz 17±1.5 dBm @ MCS6 40 MHz 17±1.5 dBm @ MCS7 40 MHz 17±1.5 dBm @ MCS8 40 MHz 17±1.5 dBm @ MCS9 40 MHz 17±1.5 dBm @ MCS10 40 MHz 17±1.5 dBm @ MCS11 40 MHz 19±1.5 dBm @ MCS12 40 MHz 19±1.5 dBm @ MCS13 40 MHz 18±1.5 dBm @ MCS14 40 MHz 18±1.5 dBm @ MCS15 40 MHz Receiver Sensitivity for 802.11a (measured at 5.680 GHz): Typ. -90 @ 6 Mbps Typ. -88 @ 9 Mbps Typ. -88 @ 12 Mbps Typ. -85 @ 18 Mbps Typ. -81 @ 24 Mbps Typ. -78 @ 36 Mbps Typ. -74 @ 48 Mbps Receiver Sensitivity for 802.11n (5 GHz): measured at 5.680 GHz: Typ. -88 dBm @ MCS0 20 MHz Typ. -85 dBm @ MCS1 20 MHz Typ. -82 dBm @ MCS2 20 MHz Typ. -79 dBm @ MCS3 20 MHz Typ. -76 dBm @ MCS4 20 MHz Typ. -71 dBm @ MCS5 20 MHz Typ. -70 dBm @ MCS6 20 MHz Typ. -69 dBm @ MCS7 20 MHz Typ. -95 dBm @ MCS8 20 MHz Typ. -91 dBm @ MCS9 20 MHz Typ. -87 dBm @ MCS10 20 MHz Typ. -80 dBm @ MCS11 20 MHz Typ. -78 dBm @ MCS12 20 MHz Typ. -74 dBm @ MCS13 20 MHz Typ. -71 dBm @ MCS14 20 MHz Typ. -71 dBm @ MCS15 20 MHz Receiver Sensitivity for 802.11g (measured at 2.437 GHz): Typ. -88 dBm @ 6 Mbps Typ. -86 dBm @ 9 Mbps Typ. -85 dBm @ 12 Mbps Typ. -85 dBm @ 18 Mbps Typ. -82 dBm @ 24 Mbps Typ. -82 dBm @ 36 Mbps Typ. -78 dBm @ 48 Mbps Typ. -74 dBm @ 54 Mbps Receiver Sensitivity for 802.11n (2.4 GHz; measured at 2.437 GHz): Typ. -89 dBm @ MCS0 20 MHz Typ. -85 dBm @ MCS1 20 MHz Typ. -85 dBm @ MCS2 20 MHz Typ. -82 dBm @ MCS3 20 MHz Typ. -78 dBm @ MCS4 20 MHz Typ. -74 dBm @ MCS5 20 MHz Typ. -72 dBm @ MCS6 20 MHz Typ. -70 dBm @ MCS7 20 MHz Typ. -95 dBm @ MCS8 20 MHz Typ. -90 dBm @ MCS9 20 MHz Typ. -87 dBm @ MCS10 20 MHz Typ. -83 dBm @ MCS11 20 MHz Typ. -80 dBm @ MCS12 20 MHz Typ. -74 dBm @ MCS13 20 MHz Typ. -74 dBm @ MCS14 20 MHz Typ. -69 dBm @ MCS15 20 MHz Typ. -87 dBm @ MCS0 40 MHz Typ. -83 dBm @ MCS1 40 MHz Typ. -83 dBm @ MCS2 40 MHz Typ. -80 dBm @ MCS3 40 MHz Typ. -76 dBm @ MCS4 40 MHz Typ. -73 dBm @ MCS5 40 MHz Typ. -69 dBm @ MCS6 40 MHz Typ. -67 dBm @ MCS7 40 MHz Typ. -93 dBm @ MCS8 40 MHz Typ. -88 dBm @ MCS9 40 MHz Typ. -85 dBm @ MCS10 40 MHz Typ. -82 dBm @ MCS11 40 MHz Typ. -78 dBm @ MCS12 40 MHz Typ. -73 dBm @ MCS13 40 MHz Typ. -69 dBm @ MCS14 40 MHz Typ. -67 dBm @ MCS15 40 MHz WLAN Operation Mode: Access point, Client, Client-Router, Sniffer Antenna Connectors: QMA Ethernet Interface PoE Ports (10/100BaseT(X)), M12 D-coded 4-pin female connector): 1, AWK-3131A-M12-RTG only Standards: IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X)- IEEE 802.3af for PoE- IEEE 802.1Q for VLAN Tagging 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector): 1, 10/100BaseT(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection (AWK-3131A-M12-RTG only) 100BaseFX Ports (single-mode SC connector): 1, AWK-3131A-SSC-RTG only Ethernet Software Features Management: - General: Proxy ARP, DNS, HTTP, HTTPS, IP, ICMP, SNMP, TCP, UDP, RADIUS, SNMP, PPPoE, DHCP- AP-only: ARP, BOOTP, DHCP, STP/RSTP (IEEE 802.1D/w) Security: RADIUS Firewall Filter: MAC/IP Protocol/Port-based Serial Interface Console Port: RS-232 (RJ45-type) LED Interface LED Indicators: PWR1, PWR2, PoE*, FAULT, STATE, SIGNAL, CLIENT, WLAN, LAN (AWK-3131A-M12-RTG only), 100M (AWK-3131A-SSC-RTG only) *PoE is only available for the AWK-3131A-M12-RTG Input/Output Interface Digital Inputs: 2- +13 to +30 V for state 1 - +3 to -30 V for state 0 Max. input current: 8 mA Alarm Contact Channels: Relay output with current carrying capacity of 1 A @ 24 VDC Buttons: Reset button Physical Characteristics Housing: Metall Rating: IP30 Dimensions: 52.9 x 151.9 x 127.4 mm (2.08 x 5.98 x 5.02 in) Weight: 850 g (1.87 lb) Installation: DIN-rail mounting, Wall mounting (with optional kit) Power Parameters Input Current: AWK-3131A-M12-RTG: 0.85 A @ 12 VDC, 0.22 A @ 48 VDC- AWK-3131A-SSC-RTG: 1.0 A @ 12 VDC, 0.27 A @ 48 VDC Input Voltage: 12 to 48 VDC, Redundant dual inputs, 48 VDC Power-over-Ethernet Power Connector: 1 removable 10-contact terminal block(s) Power Consumption: AWK-3131A-M12-RTG: Maximum 10.5 W- AWK-3131A-SSC-RTG: Maximum 13 W Reverse Polarity Protection: Supported Environmental Limits Operating Temperature: - Wide Temp. Models: -40 to 75°C (-40 to 167°F) Storage Temperature (package included): -40 to 85°C (-40 to 185°F) Ambient Relative Humidity: 5 to 95% (non-condensing) Standards and Certifications EMC: EN 61000-6-2/-6-4 EMI: CISPR 32, FCC Part 15B Class B EMS: IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 Railway: EN 50155, EN 50121-4 Railway Fire Protection: EN 45545-2 Radio: EN 301 489-1/17, EN 300 328, EN 301 893, MIC, FCC ID SLE-WAPN008, SRRC, NCC, IDA Safety: UL 60950-1, IEC 60950-1, EN 60950-1 (LVD) MTBF Time: AWK-3131A-M12-RTG: 552,454 hrs- AWK-3131A-SSC-RTG: 528,478 hrs Standards: Telcordia SR332

Specifications

Scan this QR code to view the product
All details, up-to-date prices and availability

