

Item no.: 387446

86M-5212U-T - Module for the ioPAC 8600 series, 2-port 2-wire Ethernet switch

from **904,10 EUR**

Item no.: 387446
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

Railway, wind power and offshore applications require system reliability and stability, even in harsh environments. Our ruggedised controllers and I/O products are designed for use in extreme conditions and offer versatile data acquisition and control functions. Module for the ioPAC 8600 series, 2-port 2-wire Ethernet switch, -40 to 75°C Operating temperature Input/output interface 2-wire Ethernet ports - 2 Isolation - 3k VDC or 2k Vrms Digital outputs Connection - Spring Euroblock-Terminal I/O mode - DO or PWM Ethernet interface Connection - M12 D-coded 2-pin socket Number of ports - 2 Standards - BroadR-Reach® for 10 Mbps and 100 Mbps - IEEE 802.3 for 10BaseT - IEEE 802.3u for 100BaseT(X) and 100BaseFX Performance parameters Power consumption - 79.2 mA @ 24 VDC Physical properties Dimensions - 25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in) Weight - Less than 80 g Cabling - I/O cable, 16 to 28 AWG Environmental conditions Operating temperature - -40 to 75°C (-40 to 167°F) Storage temperature (in packaging) - -40 to 85°C (-40 to 185°F) Relative humidity - 5 to 95% (non-condensing) Altitude - 2000 m Standards and certifications EMC - EN 55032/24, EN 61000-6-2/-6-4 EMI - CISPR 32, FCC Part 15B Class A EMS - IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV - IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m - IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV - IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV - IEC 61000-4-6 CS: 10 V - IEC 61000-4-8 PFMFRailway - EN 50121-4, EN 50155 Safety - UL 508 Shock - IEC 60068-2-27 Vibration - IEC 60068-2-6 MTBF Time - 2,498.942 hours Standards - Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

