

Item no.: 387422

85M-2600-T - Module for the ioPAC 85008600 series, 16 DOs, 24 VDC, sink

from **337,32 EUR**

Item no.: 387422
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

Module for the ioPAC 8500/8600 series, 16 DOs, 24 VDC, sink, -40 to 75°C Operating temperature
 Input/output interface Digital output channels- 16 Isolation- 3k VDC or 2k Vrms Digital outputs Voltage- 24 VDC 24 VDC Connector- Spring Euroblock terminal Rated current- 200 mA per channel I/O mode- DO or PWM I/O type- Sink Overcurrent protection- 0.65 A per channel at 25°C Overtemperature shutdown- 175°C (typical), 150°C (min.) Pulse output frequency- 5 kHz Overvoltage protection- 45 VDC (typical) Power parameters Power consumption- 35.4 mA @ 24 VDC Physical characteristics Dimensions- 25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in) Weight- less than 80 g Wiring- I/O cable, 14 to 28 AWG Environmental conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Altitude- 2000 m- Note: Please contact Moxa if you require products that are guaranteed to function properly at high altitudes. Standards and certifications EMC- EN 55032/24- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Railway- EN 50121-4- EN 50155 (fulfils part of the EN 50155 specifications) Safety- UL 508 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 MTBF Time- 792,571 hours Standards- Telcordia SR332

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

