

Item no.: 387426

85M-5401-T - Module for the ioPAC 85008600 series, 4 serial ports, DB44 connector

from **767,28 EUR**

Item no.: 387426
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

Railway, wind power and offshore applications require system reliability and stability, even in harsh environments. Our ruggedised controllers and I/O products are designed for use in extreme conditions and offer versatile data acquisition and control functions. Module for ioPAC 8500/8600 series, 4 serial ports, DB44 connectors, operating temperature -40 to 75°C Input/output interfacing Isolation- 3k VDC or 2k Vrms Serial ports- 4 Digital outputs Pulse output frequency- 5 kHz Serial interface Baud rate- 300 bps to 921.6 kbps Data bits- 7, 8 Flow control- RTS/CTS- XON/XOFF Parity- Even- None- Odd Serial standards- RS-232/422/485 Stop bits- 1, 2 Serial signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, GND RS-485- 2w- Data+, Data-, GND RS-485- 4w- Tx+, Tx-, Rx+, Rx-, GND Power parameters Power consumption- 51.7 mA @ 24 VDC Physical properties Dimensions- 25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in) Weight- less than 80 g Wiring- I/O cable, 14 to 28 AWG Environmental conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Altitude- 2000 m- Note: Please contact Moxa if you require products that are guaranteed to function properly at higher altitudes. Standards and certifications EMC- EN 55032/24- EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFM Railway- EN 50121-4- EN 50155 (fulfils part of the EN 50155 specifications) Safety- UL 508 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 MTBF Time- 596,611 hours Standards- Telcordia SR332

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

