

Item no.: 385608

MAT-5G-PA-SM-3-06-3M - 6 dBi MIMO panel antenna with 3 SMA (male) connectors for cellular and GNSS appl

from **429,84 EUR**

Item no.: 385608
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

Moxa offers a wide variety of cellular antennas that are easy to install and simplify the process of establishing wireless networks. 6 dBi MIMO panel antenna with 3 SMA (male) connectors for cellular and GNSS applications, 3 m cable. Antenna Characteristics- Frequency Cellular: 617 to 960, 1427 to 1510, 1710 to 2170, 2300 to 2690 MHz GNSS: 1561.00, 1575.42, 1602.00 MHz- Antenna Type Panel- Typical Antenna Gain Cellular: 2.64 dBi @ 617 to 698 MHz (5G NR n71) 5.23 dBi @ 698 to 824 MHz (LTE 700) 4.73 dBi @ 824 to 960 MHz (GSM 850/900) 6.66 dBi @ 1427 to 1510 MHz (5G NR n74,75,76) 6.14 dBi @ 1710 to 1880 MHz (DCS) 5.92 dBi @ 1850 to 1990 MHz (PCS) 5.92 dBi @ 1920 to 2170 MHz (UMTS) 5.54 dBi @ 2300 to 2690 MHz (LTE 2600) GNSS: 1.21 dBi @ 1561.00 MHz (BDS) 1.29 dBi @ 1575.42 MHz (GPS) 1.44 dBi @ 1602.00 MHz (GLONASS) With low noise amplifier: 30 dB- Connector SMA (male)- Impedance 50 ohms Polarization Linear/Vertical Physical Characteristics- Dimensions 135.95 x 135.95 x 47.44 mm (5.35 x 5.35 x 1.87 in)- Radome Material Plastic- Radome Color Black- Installation Screw mount- Cable SNC200- Cable Length 3 m- IP Rating IPx9K Environmental Limits- Operating Temperature -40 to 85°C (-40 to 185°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (30°C, non-condensing)

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

