

Item no.: 385410

NPORT IA5250A - 2-port RS-232/422/485 device server for industrial automation

from **327,86 EUR**

Item no.: 385410
 shipping weight: 0.50 kg
 Manufacturer: MOXA



Product Description

The industrial device servers offer enhanced surge protection and are certified for use in hazardous areas such as railway vehicles and roadsides. In addition, all devices are designed to ensure reliable serial-to-Ethernet connectivity when operating in harsh environments such as the oil and gas industry and energy automation.

2-Port RS-232/422/485 device server for industrial automation with overvoltage protection for serial/LAN/power, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature

Ethernet Interface- 10/100BaseT(X) ports (RJ45 connector)

Supports 2 IP addresses

Auto MDI/MDI-X connection- Magnetic Isolation Protection 1.5 kV (built-in)

Ethernet Software Features- Configuration Options

Web Console (HTTP/HTTPS), Windows Utility, Device Search Utility (DSU), MCC Tool, Serial Console, Telnet Console- Management ARP, BOOTP, DHCP Client, DNS, HTTP, HTTPS, ICMP, IPv4, LLDP, Rtelnet, SMTP, SNMPv1/v2c, TCP/IP, Telnet, UDP- Filter IGMP v1/v2- Linux Real TTY Drivers Kernel versions: 2.4.x, 2.6.x, 3.x, 4.x, and 5.x- Fixed TTY Drivers SCO UNIX, SCO OpenServer, UnixWare 7, QNX 4.25, QNX 6, Solaris 10, FreeBSD, AIX 5.x, HP-UX 11i, Mac OS X, macOS 10.12, macOS 10.13, macOS 10.14, macOS 10.15- Android API Android 3.1.x and later- Time Management

SNTP- Windows Real COM Drivers

Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10/11 (x86/x64), Windows 2008 R2/2012/2012 R2/2016/2019 (x64), Windows Server 2022, Windows Embedded CE 5.0/6.0, Windows XP Embedded

Security Functions- Authentication Local database- Encryption HTTPS, AES-128, RSA-1024, SHA-1, SHA-256

Serial Interface- Connector DB9 male- No. of Ports 2- Serial Standards RS-232, RS-422, RS-485- Operation Modes Disabled, Ethernet Modem, Pair Connection, Real COM, Reverse Telnet, RFC2217, TCP Client, TCP Server, UDP- Baudrate Supports standard baudrates (unit=bps): 50, 75, 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 19200, 38400, 57600, 115200, 230.4k, 460.8k, 921.6k- Data Bits 5, 6, 7, 8- Stop Bits 1, 1.5, 2- Parity None, Even, Odd, Space, Mark- Flow Control None, RTS/CTS (RS-232 only), DTR/DSR (RS-232 only), XON/XOFF- Pull High/Low Resistor for RS-485 1 kilo-ohm, 150 kilo-ohms- Terminator for RS-485 120 ohms- RS-485 Data Direction Control ADDC (automatic data direction control)

Serial Signals- RS-232 Tx+, Tx-, Rx+, Rx-, GND- RS-422 Tx+, Tx-, Rx+, Rx-, GND- RS-485-4w Tx+, Tx-, Rx+, Rx-, GND- RS-485-2w Data+, Data-, GND

Power Parameters- Input Current 250 mA @ 12 VDC- Input Voltage 12 to 48 VDC- No. of Power Inputs 2- Power Connector Terminal block

Physical Characteristics- Housing Metal- Dimensions 36 x 105 x 140 mm (1.42 x 4.13 x 5.51 in)- Weight 485 g (1.07 lb)- Installation DIN-rail mounting, Wall mounting (with optional kit)

Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -40 to 75°C (-40 to 167°F)- Ambient Relative Humidity 5 to 95% (non-condensing)

Standards and Certifications- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMSIEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/mIEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kVIEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kVIEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/mIEC 61000-4-8 PFMFIEC 61000-4-11- Hazardous Locations ATEX Zone 2, UL/cUL Class I Division 2 Groups A/B/C/D- Safety UL 508- Vibration IEC 60068-2-6- Shock IEC 60068-2-27- Freefall IEC 60068-2-32

Declaration- Green Product RoHS, CRoHS, WEEE/MTBF- Time 262,805 hrs- Standards Telcordia (Bellcore) Standard TR/SR

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

