

Item no.: 385680

EOM-104 - Embedded managed Ethernet switch module with 4 10100BaseT(X) ports, -40 to 75C o

from **224,45 EUR**

Item no.: 385680
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Our Ethernet embedded modules are designed for device manufacturers who want to enhance the performance and reliability of their solutions, and want to make them suitable for use in applications with harsh conditions. Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, -40 to 75°C operating temperature Ethernet Interface- Standards IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3x for flow control IEEE 802.1p for Class of Service IEEE 802.1D-2004 for Spanning Tree Protocol IEEE 802.1w for Rapid Spanning Tree Protocol- 10/100BaseT(X) Port 4- Connector 1 connector with 2 x 20 pins, 2 connectors with 1 x 9 pins, and 1 connector with 2 x 2 pins- GPIO 4 x Programmable I/O pins Ethernet Software Features- Protocols BOOTP, DHCP Client, HTTP, RARP, RMON, SMTP, SNMPv1/v2c/v3, Syslog, Telnet, TFTP- MIB Bridge MIB, Ethernet-like MIB, MIB-II, P-BRIDGE MIB, RMON MIB Groups 1, 2, 3, 9, RSTP MIB Switch Properties- MAC Table Size 1 K- Packet Buffer Size 512 kbits Serial Interface- Console Port RS-232 (TxD, RxD, DTR, DSR) Power Parameters- Input Current 0.48 A @ 3.3 VDC Physical Characteristics- Dimensions 54 x 60 x 8.25 mm (2.13 x 2.36 x 0.32 in)- Weight 21 g (0.046 lb) Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

