

Item no.: SC-2406-1113-4726 JVS-ND7004-PD01 - PoE 4-Channel H.265 4K NVR, for Cameras up to 5 MP

84,92 EUR

Item no.: SC-2406-1113-4726 shipping weight: 1.10 kg Manufacturer: Jovision



Product Description

JVS-ND7004-PD01 - PoE 4-Channel H.265 4K NVR, for Cameras up to 5 MP Jovision 4-channel Network Video Recorder for cameras up to 5 MP. Key Features:

- Adopts the new Vstar GUI, easy to operate
 Supports intelligent coding VSMart, greatly reducing storage space
 Improved compatibility for hard disks, and up to 10 TB
 Supports Intelligent Detection and Human Detection

- Supports face capture, face comparison, and efficient comparison of face information
 Supports face search by face, deduplication, and precise playback
 Supports full PoE camera access, support 4x PoE + 4 non-PoE accesses (a total of 8)

Video and Audio

- IP Camera Input: 4-channel PoE cameras up to 5 MP + 4-channel non-PoE cameras up to 5 MP
- Audio I/O: 1-channel output RCA: Audio output support HDMI

Display

- Interface: 1x HDMI, 1x VGA
- Resolution: HDMi, 18 V0710, 1920x1080, 2560x1440, 1440x900, 1280x1024, 1280x720, 1024x768
 VGA: 1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768
 Multi-screen display: Port binding 4; Non-port bonding 1/4/5/6/7/8/9

- OSD: Camera name & time, recording, alarm detecting, remote connection, volume, channel number

Recording

- Compression: H.265/H.264
 Resolution: 6-channel 5.0 MP/4.0 MP/1080P/960P/720P
- Record mode: Manual, schedule, MD

Video Detection and Alarm

- Trigger events: Recording, snapshot, PTZ, voice, e-mail, client, buzzer
- Video detection: Motion detection. no video detection

Playback and Backup

- Sync playback: 2-channel 5.0 MP/3-channel 4.0 MP/4-channel 3.0 MP
- Search mode: Time/date, schedule, motion detection
 Playback function: Day view, hour view, back step, rewind, pause, play, fast forward, slow, step, full screen, snap, sound on/off, zoom
 Backup mode: USB device/network
- USB: 2x USB 2.0

- Interface: 1x RJ-45 port (10/100/1000 Mbps)
 PoE interface: 4-port 100 Mbps IEEE 802.3af PoE
 Network function: TCP/IP, DHCP, UDP, SMTP, NTP
 Smartphone: iPhone, Android
 Interoperability: ONVIF 2.4

Storage

- SATA: 11x SATA interface
 Capacity: Up to 10 TB

<u>General</u>

- Power supply: 52 V DC
 Consumption: ? 50 W (without HDD)
 Working temperature: -10°C ~ 55°C
 Working humidity: 10% ~ 90%
 Dimensions: 260 x 219 x 45 mm
 Weight: ? 1.05 kg (without HDD)

Specifications



