

Item no.: 387945

TN-5308-LV-T - Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors

from **480,43 EUR**

Item no.: 387945
 shipping weight: 0.50 kg
 Manufacturer: MOXA



Product Description

Moxa is an IRIS-certified company that offers an extensive portfolio of robust Ethernet switches that fulfil the mandatory sections of the EN 50155 standard. These products are used in many railway and metro systems around the world. With our innovative solutions and technologies, we help train builders to increase overall traffic safety and efficiency as well as achieve significant cost and time savings in the operation and maintenance of railway vehicles.

Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 7 to 60 VDC, -40 to 75°C operating temperature, M12 power cable Ethernet Interface- 10/100BaseT(X) ports (M12 D-coded 4-pin female connector) 8- Standards IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) IEEE 802.3x for flow control Power Parameters- Input Current 0.19 A @ 12 VDC, 0.10 A @ 24 VDC, 0.054 A @ 48 VDC- Input Voltage 12 to 48 VDC- No. of Power Inputs 1- Operating Voltage 8.4 to 60 VDC- Power Connector M12 A-coded male connector Physical Characteristics- Housing Metal- IP Rating IP40- Dimensions 60 x 216.6 x 36.1 mm (2.36 x 8.53 x 1.42 in)- Weight Packaged: 485 g (1.07 lb)- Installation DIN-rail mounting (with optional kit) Wall mounting Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Altitude 2000 m Standards and Certifications- Freefall IEC 60068-2-32- EMC EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1, EN 50155 IEC 60068-2-14, EN 50155 IEC 60068-2-2, EN 50155 IEC 60068-2-30, EN 50155- International Approval RCM- Railway EN 50121-4 EN 50155- Railway Fire Protection EN 45545-2- Safety EN 60950-1 UL 508- Salt Spray Test IEC 60068-2-11, EN 50155- Shock IEC 60068-2-27, IEC 61373, EN 50155- Vibration IEC 60068-2-64, IEC 61373, EN 50155 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 2,804,342 hrs- Standards Telcordia SR332

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

