

Item no.: 387898

## SFP-1G40ALC - WDM type (BiDi) SFP module with 1 1000BaseSFP port with LC connection for 40 km

from **1.252,99 EUR**

Item no.: 387898  
 shipping weight: 0.10 kg  
 Manufacturer: MOXA



### Product Description

Moxa's Small Form-Factor Pluggable Transceiver (SFP) Ethernet fibre optic modules for Gigabit Ethernet provide coverage over a wide range of communication distances. WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C Operating temperature Ethernet Interface- Ports 1- Connectors Duplex LC connector Simplex LC connector (WDM-type only)- Optical Fiber Typical Distance: To reach the typical distance of specified fibre transceiver, please refer to formula: Link budget(dB) > dispersion penalty(dB) + total link loss(dB) Power Parameters- Power Consumption Max. 1 W Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- Safety UL 62368-1 IEC 62368-1 IEC 60825-1- EMC EN 55032/35- EMIFCC 15B Test Report IECES-003: 2020 Issue 7- EMS IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV(AC), 0.5 kV(DC); Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 1 kV / 2 kV(AC), 0.5 kV(DC); Signal: 1 kV IEC 61000-4-6 CS: 0.15 MHz to 10 MHz: 3 V, 10 MHz to 30 MHz: 3 to 1 V, 30 MHz to 80 MHz: 1V IEC 61000-4-8 PFMF: 1 A/m at 50 Hz IEC 61000-4-11 Voltage Dips and Interruption

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

