

Item no.: 385639

85M-BKTES - Empty slot cover (3 pieces per pack)

from **59,36 EUR**

Item no.: 385639
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Railway, wind power and offshore applications require system reliability and stability, even in harsh environments. Our robust controllers and I/O products are designed for use in extreme conditions and offer versatile data acquisition and control functions. Empty slot cover (3 per package) Input/Output Interface- Isolation 3k VDC or 2k Vrms Digital Outputs- Pulse Output Frequency 5 kHz Physical Characteristics- Dimensions 25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in)- Weight Under 80 g- Wiring I/O cable, 14 to 28 AWG Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)- Altitude 2000 m Note: Please contact Moxa if you require products guaranteed to function properly at higher altitudes. Standards and Certifications- EMC EN 55032/24 EN 61000-6-2/-6-4- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Railway EN 50121-4 EN 50155 (complies with a portion of EN 50155 specifications)- Safety UL 508- Shock IEC 60068-2-27- Vibration IEC 60068-2-6 MTBF- Standards Telcordia SR332

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

