

Item no.: 387448

A53-DB9F W/ ADAPTER - RS-232/422/485 converter with 2 kV insulation, adapter, DB9F cable

from **90,64 EUR**

Item no.: 387448
 shipping weight: 0.20 kg
 Manufacturer: MOXA



Product Description

RS-232/422/485 converter with 2 kV isolation, adapter, DB9F cable
 Serial interface Connector- 10-pin RJ45 Flow control- RTS/CTS Isolation- 2 kV Number of ports- 2 RS-485 data direction control- ADDC (automatic data direction control) Serial standards- RS-232- RS-422- RS-485 Serial signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND RS-422- Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND RS-485-2w- Data+, Data-, GND Performance parameters Input current- 195 mA @ 9 VDC Input voltage- 9 to 30 VDC Number of current inputs- 1 Overload protection- Supported Power consumption- 195 mA @ 9 VDC Source of input power- Current input socket Physical properties Housing- Plastic IP protection class- IP30 Dimensions- 90 x 60 x 21 mm (3.54 x 2.36 x 0.83 in)- 85 g (0.19 lb) Installation- Desktop Environmental conditions Operating temperature- 0 to 55°C (32 to 131°F) Storage temperature (including packaging)- -20 to 75°C (-4 to 167°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF Environmental tests- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3 Vibration- IEC 60068-2-6 MTBF Time- 1.870,854 hours Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

