

Item no.: 387594

## A52-DB25F W/ ADAPTER - RS-232/422/485 converter with adapter, DB25F cable

from **62,32 EUR**

Item no.: 387594  
 shipping weight: 0.10 kg  
 Manufacturer: MOXA



### Product Description

RS-232/422/485 converter with adapter, DB25F cable  
 Serial Interface Connector- 10-pin RJ45  
 Flow Control- RTS/CTS  
 No. of Ports- 2  
 RS-485 Data Direction Control- ADDC (automatic data direction control)  
 Serial Standards- RS-232- RS-422- RS-485  
 Serial SignalsRS-232- TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND  
 RS-422- Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND  
 RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND  
 RS-485-2w- Data+, Data-, GND  
 Power ParametersInput Current- 170 mA @ 9 VDC  
 Input Voltage- 9 to 30 VDC  
 No. of Power Inputs- 1  
 Overload Current Protection- Supported  
 Power Consumption- 170 mA @ 9 VDC  
 Source of Input Power- Power input jack  
 Physical CharacteristicsHousing- Plastic  
 IP Rating- IP30  
 Dimensions- 90 x 60 x 21 mm (3.54 x 2.36 x 0.83 in)  
 Weight- 85 g (0.19 lb)  
 Installation- Desktop  
 Environmental LimitsOperating Temperature- 0 to 55°C (32 to 131°F)  
 Storage Temperature (package included)- -20 to 75°C (-4 to 167°F)  
 Ambient Relative Humidity- 5 to 95% (non-condensing)  
 Standards and CertificationsEMC- EN 55032/35  
 EMI- CISPR 32, FCC Part 15B Class A  
 EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFM  
 Environmental Testing- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3  
 Vibration- IEC 60068-2-6  
 MTBFTime- 1,870,854 hrs  
 Standards- Telcordia (Bellcore), GB

### Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

