

Item no.: 387447

86M-5250-T - Module for the ioPAC 8600 Series, 2 CAN ports, -40 to 75C operating temperature

from **497,68 EUR**

Item no.: 387447
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Module for the ioPAC 8600 Series, 2 CAN ports, -40 to 75°C operating temperature
Input/Output Interface CAN Ports- 2 Isolation- 3k VDC or 2k Vrms Digital Outputs Connector- Spring-type Euroblock terminal I/O Mode- DO or PWM CAN Interface Industrial Protocols- CAN 2.0A, CAN 2.0B, CANopen DS301, V4.02 Baudrate- 10/20/50/125/250/500/800/1000 kbps, user-defined Connector- DB9 male Isolation- 3k VDC or 2k Vrms No. of Ports- 2 Terminator- N/A, 120 ohms (by DIP) Power Parameters Power Consumption- 60.0 mA @ 24 VDC Physical Characteristics Dimensions- 25 x 128.2 x 85.5 mm (0.98 x 5.05 x 3.37 in) Weight- Under 80 g Wiring- I/O cable, 16 to 28 AWG Environmental Limits Operating Temperature- -40 to 75°C (-40 to 167°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Altitude- 2000 m Standards and Certifications EMC- EN 55032/24, EN 61000-6-2/-6-4 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFM Railway- EN 50121-4, EN 50155 Safety- UL 508 Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 MTBF Time- 3,306,609 hrs Standards- Telcordia SR332

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

