

Item no.: 387434

A53-DB25F W/ ADAPTER - RS-232/422/485 converter with 2 kV insulation, adapter, DB25F cable

from **90,64 EUR**

Item no.: 387434
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

RS-232/422/485 converter with 2 kV isolation, adapter, DB25F cable
 Serial interface Connector- 10-pin RJ45
 Flow control- RTS/CTS
 Isolation- 2 kV
 Number of ports- 2
 RS-485 data direction control- ADDC (automatic data direction control)
 Serial standards- RS-232- RS-422- RS-485
 Serial signals RS-232- Tx, D, Rx, D, RTS, CTS, DTR, DSR, DCD, GND
 RS-422- Tx+, Tx-, Rx+, Rx-, RTS+, RTS-, CTS+, CTS-, GND
 RS-485-4w- Tx+, Tx-, Rx+, Rx-, GND
 RS-485-2w- Data+, Data-, GND
 Performance parameters
 Input current- 195 mA @ 9 VDC
 Source of input power- Current input socket
 Physical properties
 Housing- Plastic
 IP protection class- IP30
 Dimensions- 90 x 60 x 21 mm (3.54 x 2.36 x 0.83 in)- 85 g (0.19 lb)
 Installation- Desktop
 Environmental conditions
 Operating temperature- 0 to 55°C (32 to 131°F)
 Storage temperature (including packaging)- -20 to 75°C (-4 to 167°F)
 Relative humidity- 5 to 95% (non-condensing)
 Standards and certifications
 EMC- EN 55032/35
 EMI- CISPR 32, FCC Part 15B Class A
 EMS- IEC 61000-4-2
 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3
 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4
 EFT: Power: 1 kV; Signal: 0.5 kV- IEC 61000-4-5
 Surge: Power: 1 kV- IEC 61000-4-6
 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8
 PFMF
 Environmental tests- IEC 60068-2-1- IEC 60068-2-14- IEC 60068-2-2- IEC 60068-2-3
 Vibration- IEC 60068-2-6
 MTBF Time- 1.870,854 hours
 Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

