

Item no.: 385760

## DK-UP-14168 - DIN-rail kit with 2 plates (89 x 19 mm), 6 screws (FMS M3 x 5 mm) for the UPort

from **42,48 EUR**

Item no.: 385760  
 shipping weight: 0.10 kg  
 Manufacturer: MOXA



### Product Description

Moxa's UPort USB-to-serial converters provide computers with high performance, industrial-grade connections for up to 16 serial devices over a single USB port. A wide range of converters are available with features that include SuperSpeed USB 3.2 and Hi-Speed USB 2.0, advanced UARTs for high-end serial performance, COM port mapping, fixed-base COM functionality, and more. DIN-rail kit with 2 plates (89 x 19 mm), 6 screws (FMS M3 x 5 mm) for the UPort 1400 (V1.5.0 and after) and 1600-8 (V1.4.0 and after) models. USB Interface Speed- 12 Mbps, 480 Mbps. USB Connector- USB Type B. USB Standards- USB 1.1/2.0 compliant. Serial Interface Connector- DB9 male. Baudrate- 50 bps to 921.6 kbps. Data Bits- 5, 6, 7, 8. Stop Bits- 1, 1.5, 2. Parity- None, Even, Odd, Space, Mark. Flow Control- None. RTS/CTS- XON/XOFF. Serial Signals RS-232- Tx, Rx, RTS, CTS, DTR, DSR, DCD, GND. RS-422- Tx+, Tx-, Rx+, Rx-, GND. RS-485- 4w- Tx+, Tx-, Rx+, Rx-, GND. RS-485- 2w- Data+, Data-, GND. Serial Software Features. Windows Drivers- Windows 11/10/8.1/8/7/Vista/XP/ME/98/95- Windows Server 2022/2019/2016/2012 R2/2012/2008 R2/2008/2003/2000/NT. Linux Drivers- Kernel versions: 6.x, 5.x, 4.x, 3.x, 2.6.x and 2.4.x. Mac Drivers- macOS versions: 10.12 to 10.15, 11.x. Virtual Machine- VMware Fusion (Windows on macOS 10.12 to 11.x)- VMWare ESXi (Linux kernel 4)- Parallels Desktop (Windows on macOS 10.12 to 11.x). Arm®-based Platform Support- Linux kernel 5.x / 4.x. Android API- Android 3.1.x and later. Physical Characteristics. Housing- Metal. Environmental Limits. Storage Temperature (package included)- -20 to 75°C (-4 to 167°F). Ambient Relative Humidity- 5 to 95% (non-condensing). Standards and Certifications. EMC- EN 55032/35. EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV- IEC 61000-4-5 Surge: Power: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m- IEC 61000-4-8 PFM. Declaration. Green Product- RoHS, CRoHS, WEEE

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

