

Item no.: 387972

EDS-2008-EL - Unmanaged Fast Ethernet switch with 8 10100BaseT(X) ports, 122448 power input, m

from **140,17 EUR**

Item no.: 387972
shipping weight: 0.20 kg
Manufacturer: MOXA



Product Description

Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature Ethernet Interface 10/100BaseT(X) Ports (RJ45 connector)- EDS-2008-EL: 8- EDS-2008-EL-M-ST: 7- EDS-2008-EL-M-SC: 7- Full/Half duplex mode- Auto MDI/MDI-X connection- Auto negotiation speed 100BaseFX Ports (multi-mode SC connector)- EDS-2008-EL-M-SC: 1100BaseFX Ports (multi-mode ST connector)- EDS-2008-EL-M-ST: 1 Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control- IEEE 802.1p for Class of Service Switch Properties Processing Type- Store and Forward MAC Table Size- 2 K Packet Buffer Size- 768 kbits DIP Switch Configuration Ethernet Interface- Quality of Service (QoS) , Broadcast Storm Protection (BSP) Power Parameters Connection- 1 removable 2-contact terminal block(s) Input Current- EDS-2008-EL: 0.052A @ 24 VDC- EDS-2008-EL-M-ST/EDS-2008-EL-M-SC: 0.082A @ 24 VDC Input Voltage- 12/24/48 VDC Operating Voltage- 9.6 to 60 VDC Overload Current Protection- Supported Reverse Polarity Protection- Supported Physical Characteristics Installation- DIN-rail mounting- Wall mounting (with optional kit) Weight- 169 g (0.37 lb) Housing- Metal Dimensions- EDS-2008-EL: 36 x 81 x 65 mm (1.4 x 3.19 x 2.56 in)- EDS-2008-EL-M-ST: 36 x 81 x 70.9 mm (1.4 x 3.19 x 2.79 in) (w/ connector)- EDS-2008-EL-M-SC: 36 x 81 x 68.9 mm (1.4 x 3.19 x 2.71 in) (w/ connector) Environmental Limits Ambient Relative Humidity- 5 to 95% (non-condensing) Operating Temperature- EDS-2008-EL/EDS-2008-EL-M-SC/EDS-2008-EL-M-ST: -10 to -60°C (14 to 140°F) EDS-2008-EL-T/EDS-2008-EL-M-SC-T/EDS-2008-EL-M-ST-T: -40 to 75°C (-40 to 167°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Standards and Certifications Safety- UL 61010-2-201- EN 62368-1 EMC- EN 55032/35- EN 61000-6-2/-6-4 EMI- CISPR 22, 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Shock- IEC 60068-2-27 Vibration- IEC 60068-2-6 Freefall- IEC 60068-2-32 MTBF Time- 3,696,394 hrs Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

