

Item no.: 387472

CB-108 - PC104-Plus bus, RS-232 module with 8 connections

from **244,12 EUR**

Item no.: 387472
 shipping weight: 0.10 kg
 Manufacturer: MOXA



Product Description

PC/104-Plus bus, 8-port RS-232 module, 0 to 55°C operating temperature
 Serial interface Comm. Controller- 16C550C or compatible x 4
 Bus- PC/104-Plus bus
 Connector- 40-pin header
 DIP switch- Serial interface
 IRQ- Assigned by BIOS
 I/O address- Assigned by BIOS
 FIFO- 128 bytes
 Max. Number of cards per PC- 8
 Number of ports- 8
 Serial standards- RS-232
 Baud rate- 50 bps to 921.6 kbps
 Data bits- 5, 6, 7, 8
 Stop bits- 1, 1.5, 2
 Parity- None, Even, Odd, Space, Mark
 Flow control- None, RTS/CTS, XON/XOFF
 Serial signals RS-232- TxD, Rx D, RTS, CTS, DTR, DSR, DCD, GND
 Performance parameters
 Input current- 153 mA @ 5 VDC
 Input voltage- 5 VDC
 Physical properties
 Dimensions- 90 x 96 mm (3.54 x 3.78 in)
 LED interface
 LED indicators- Built-in Tx, Rx LEDs for each port
 Environmental conditions
 Operating temperature- 0 to 55°C (32 to 131°F)
 Storage temperature (included)- -40 to 85°C (-40 to 185°F)
 Relative humidity- 5 to 95% (non-condensing)
 Standards and certifications
 EMC- EN 55032/24
 EMI- CISPR 32, FCC Part 15B Class A
 EMS- IEC 61000-4-2
 ESD: Contact: 4 kV; Air: 8 kV- IEC 61000-4-3
 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4
 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5
 Surge: Power: 0.5 kV- IEC 61000-4-6
 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8
 PFM
 Environmental tests- IEC 60068-2-1- IEC 60068-2-2- IEC 60068-2-3- IEC 60068-2-14
 Vibration- IEC 60068-2-6
 MTBF Time- 403.631 hours
 Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

