

Item no.: 387609

EDS-P206A-4POE-SS-SC - Unmanaged Ethernet switch with 1 10/100BaseT(X) port

from **678,74 EUR**

Item no.: 387609
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Moxa has an extensive portfolio of industrial unmanaged switches specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches fulfil the stringent standards required for operational reliability in harsh environments. Unmanaged Ethernet switch with 1 10/100BaseT(X) port, 4 PoE ports and 2 100BaseFX single-mode ports with SC connection, -10 to 60 °C operating temperature Ethernet interface 100BaseFX ports (single-mode SC connection)- 2PoE ports (10/100BaseT(X), RJ45 connection)- 4- Speed with automatic negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection Standards- IEEE 802.3 for 10BaseT- IEEE 802.3af/at for PoE/PoE+ output- IEEE 802.3x for flow control- IEEE 802.3u for 100BaseT(X) PoE Pinout- V+, V+, V-, V- for Pins 1, 2, 3, 6 (Endspan, MDI, Mode A) Fibre Optic Switch Features Packet Buffer Size- 768 kbits MAC Table Size- 2 K Processing Type- Store and Forward Power Parameters Input Current- 5.55 A @ 24 VDC Connection- 1 detachable 4-contact terminal block(s) Operating Voltage- 12 to 57 VDC Input Voltage- 12/24/48 VDC- Redundant Dual Inputs Power Budget- Max. 120 W for total PD consumption- Max. 30 W for each PoE port Power consumption (max.)- Max. 13.2 W at full load without PD consumption Reverse polarity protection- Supports Overload protection- Supports Physical characteristics Housing- Metall IP protection- IP30 Dimensions- 50.3 x 114 x 70 mm (1.98 x 4.53 x 2.76 in) Weight- 375 g (0.83 lb) Installation- DIN rail mounting- wall mounting (with optional kit) Environmental conditions Operating temperature- -10 to 60°C (14 to 140°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMI- CISPR 32, FCC Part 15B Class A EMC- EN 55032/24 EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMFSafety- UL 508 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-31 Vibration- IEC 60068-2-6 MTBF Time- 1,289,258 hours Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

