

Item no.: 387811

## EDS-208A-M-SC - Unmanaged Ethernet switch with 7 10/100BaseT(X) ports

from **266,08 EUR**

Item no.: 387811  
shipping weight: 0.50 kg  
Manufacturer: MOXA



### Product Description

Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multimode port with SC connector, -10 to 60°C operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 7- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection 100BaseFX ports (multi-mode SC connector)- 1 Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control Switch characteristics MAC table size- 2 K Packet buffer size- 768 kbits Processing type- Store and Forward Power supply parameters Connection- 1 detachable 4-contact terminal block(s) Input current- 0.11 A @ 24 VDC Input voltage- 12/24/48 VDC- Redundant dual inputs Operating voltage- 9.6 to 60 VDC Overload current protection- Supports Reverse polarity protection- Supports DIP switch configuration Ethernet interface- Broadcast storm protection Physical properties Housing- Aluminium IP protection- IP30 Dimensions- 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in) Weight- 275 g (0.61 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Ambient conditions Operating temperature- -10 to 60°C (14 to 140°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- EN 62368-1 (LVD) EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Hazardous areas- ATEX- Class I Division 2 Railway- EN 50121-4 Traffic control- NEMA TS2 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Free fall- IEC 60068-2-31 Marine- ABS- LR- NK- DNVMTB Time- EDS-208A: 3,248,014 hours- EDS-208A-MM/SS: 2,705,157 hours- EDS-208A-M/S: 2,943,335 hours Standards- Telcordia (Bellcore), GB

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

