

Item no.: 387817

## EDS-208A-SS-SC - Unmanaged Ethernet switch with 6 10/100BaseT(X) ports

from **554,30 EUR**

Item no.: 387817  
 shipping weight: 0.50 kg  
 Manufacturer: MOXA



### Product Description

Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60 °C operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connection) - 6 - Automatic speed negotiation - Full/half-duplex mode - Automatic MDI/MDI-X connection 100BaseFX ports (single-mode SC connection) - 2 Standards - IEEE 802.3 for 10BaseT - IEEE 802.3u for 100BaseT(X) and 100BaseFX - IEEE 802.3x for flow control Switch properties MAC table size - 2 K Packet buffer size - 768 kbits Processing type - Store and Forward Power supply parameters Connection - 1 detachable 4-contact terminal block(s) Input current - 0.15 A @ 24 VDC Input voltage - 12/24/48 VDC - Redundant dual inputs Operating voltage - 9.6 to 60 VDC Overload current protection - Supports Reverse polarity protection - Supports DIP switch configuration Ethernet interface - Broadcast storm protection Physical properties Housing - Aluminium IP protection - IP30 Dimensions - 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in) Weight - 275 g (0.61 lb) Installation - DIN rail mounting - Wall mounting (with optional kit) Ambient conditions Operating temperature - -10 to 60 °C (14 to 140 °F) Storage temperature (including packaging) - -40 to 85 °C (-40 to 185 °F) Relative humidity - 5 to 95% (non-condensing) Standards and certifications Safety - UL 508 - EN 62368-1 (LVD) EMC - EN 55032/35 EMI - CISPR 32, FCC Part 15B Class A EMS - IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV - IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m - IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV - IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV - IEC 61000-4-6 CS: 10 V - IEC 61000-4-8 PFMF Hazardous areas - ATEX - Class I Division 2 Railway - EN 50121-4 Traffic control - NEMA TS2 Vibration - IEC 60068-2-6 Shock - IEC 60068-2-27 Free fall - IEC 60068-2-31 Marine - ABS - LR - NK - DNV MTBF Time - EDS-208A: 3,248,014 hours - EDS-208A-MM/SS: 2,705,157 hours - EDS-208A-M/S: 2,943,335 hours Standards - Telcordia (Bellcore), GB

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

