

Item no.: 387809

EDS-208A-MM-ST - Unmanaged Ethernet switch with 6 10/100BaseT(X) ports

from **351,85 EUR**

Item no.: 387809
shipping weight: 0.50 kg
Manufacturer: MOXA



Product Description

Moxa has a large portfolio of industrial unmanaged switches specifically designed for industrial Ethernet infrastructure. Our unmanaged Ethernet switches meet the stringent standards required for operational reliability in harsh environments. Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multimode ports with ST connectors, -10 to 60°C operating temperature Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multimode ports with ST connectors, -10 to 60°C operating temperature Ethernet interface-10/100BaseT(X) ports (RJ45 connector): 6, automatic speed negotiation, full/half duplex mode, automatic MDI/MDI-X connection-100BaseFX ports (ST multimode connector): 2-Standards: IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) and 100BaseFX IEEE 802.3x for flow control-Optical Fibre Switch features MAC Table Size: 2 K Packet Buffer Size: 768 kbits Processing Type: Store and Forward Performance parameters Connection: 1 detachable 4-contact terminal block(s) Input current: 0.15 A @ 24 VDC Input voltage: 12/24/48 VDC, redundant dual inputs Operating voltage: 9.6 to 60 VDC Overload current protection: Supported Reverse polarity protection: Supported DIP switch configuration Ethernet interface: Broadcast storm protection Physical properties Housing: Aluminium IP protection class: IP30 Dimensions: 50 x 114 x 70 mm (1.96 x 4.49 x 2.76 in) Weight: 275 g (0.61 lb) Installation: DIN rail mounting, wall mounting (with optional kit) Environmental conditions Operating temperature: -10 to 60°C (14 to 140°F) Storage temperature (including packaging): -40 to 85°C (-40 to 185°F) Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications Safety: UL 508, EN 62368-1 (LVD) EMC: EN 55032/35 EMI: CISPR 32, FCC Part 15B Class A EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF Potentially explosive atmospheres: ATEX, Class I Division 2 Railway: EN 50121-4 Traffic control: NEMA TS2 Vibration: IEC 60068-2-6 Shock: IEC 60068-2-27 Free fall: IEC 60068-2-31 Marine: ABS, LR, NK, DNV MTBF- Time EDS-208A: 3,248,014 hrs. EDS-208A-MM/SS: 2,705,157 hrs. EDS-208A-M/S: 2,943,335 hrs.- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

