

Item no.: 387850

EDS-308-M-SC-T - Unmanaged Ethernet switch with 7 10/100BaseT(X) ports

from **355,10 EUR**

Item no.: 387850
shipping weight: 0.50 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multimode ports with SC connectors, relay output Warning, -40 to 75 °C operating temperature Input/output interface Alarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDC Ethernet interface 10/100BaseT(X) ports (RJ45 connection) ports (RJ45 connection)- 6- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection 100BaseFX ports (multi-mode SC connection)- 2 standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow control DIP switch configuration Ethernet interface- Port break alarm Switch properties MAC table size- 2 kbits Packet buffer size- 768 K Processing type- Store and Forward Power supply parameters Input current- 0.15 A @ 24 VDC Connection- 1 removable 6-contact terminal block(s) Operating voltage- 9.6 to 60 VDC- Input voltage Redundant dual inputs- 12/24/48 VDC Reverse polarity protection- Supported Overload current protection- Supported Physical properties Housing- Metall IP protection class- IP30 Dimensions- 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in) Weight- 790 g (1.75 lb) Installation- DIN rail mounting- Wall mounting (with optional kit) Ambient conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 85°C (-40 to 85°C) -40 to 85°C (-40 to 185°F) Ambient relative humidity- 5 to 95% (non-condensing) Standards and certifications Safety- UL 508- UL 60950-1 CSA C22.2 No. 60950-1- EN 62368 (LVD) EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 MHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V Hazardous areas- ATEX- Class I Division 2- Vibration IEC 60068-2-6- Shock IEC 60068-2-27- Free fall IEC 60068-2-32- Maritime- DNVMTB Time- 2.382,553 hrs Standards MIL-HDBK-217F

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

