

Item no.: 387724

EDS-316-MM-SC - Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX

from **660,13 EUR**

Item no.: 387724
shipping weight: 1.20 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multimode ports with SC connectors, relay output Warning, -10 to 60 °C operating temperatureInput/output interfaceAlarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDCEthernet interface10/100BaseT(X) ports (RJ45 connection)ports (RJ45 connection)- 14- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection100BaseFX ports (multi-mode SC connection)- 2standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow controlDIP switch configurationEthernet interface- Port break alarmSwitch propertiesPacket buffer size- 1.25 MbitsMAC Table Size- 4 KProcessing Type- Store and ForwardPower ParametersInput Voltage- 12/24/48 VDC- Redundant dual inputsInput Current- 0.39 A @ 24 VDCConnection- 1 removable 6-contact terminal block(s)Operating Voltage- 9.6 to 60 VDCReverse polarity protection- SupportsOverload current protection- SupportsPhysical propertiesHousing- MetallIP protection class- IP30Dimensions- 80.1 x 135 x 105 mm (3.15 x 5.31 x 4.13 in)Weight- 1140 g (2.52 lb)Installation- DIN rail mounting- Wall mounting (with optional kit)Ambient conditionsOperating temperature-10 to 60°C (14 to 140°F)Storage temperature (including packaging)-40 to 85°C (-40 to 185°F)Ambient relative humidity5 to 95% (non-condensing)Standards and certificationsSafety- EN 62368-1- UL 508- UL 60950-1- CSA C22.2 No. 60950-1EMC- EN 55032/35EMI- CISPR 32, FCC Part 15B Class AEMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 MHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMFHazardous areas- ATEX- Class I Division 2Vibration- IEC 60068-2-6Shock- IEC 60068-2-27Free fall- IEC 60068-2-32Maritime area- DNVMTBF time- 1.904,659 hrsStandards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

