

Item no.: 387523

## IOPAC 8600-BM005-T - Module for the ioPAC 8600 series, 5 slots, -40 to 75C operating temperature

from **875,15 EUR**

Item no.: 387523  
shipping weight: 2.60 kg  
Manufacturer: MOXA



### Product Description

Railway, wind power and offshore applications require system reliability and stability, even in harsh environments. Our robust controllers and I/O products are designed for use in extreme conditions and offer versatile data acquisition and control functions. Module for the ioPAC 8600 series, 5 slots, -40 to 75°C operating temperature Security functions- Authentication: Local database- Encryption: AES-256 HMAC RSA-1024 SHA-1 SHA-256- Security protocols: SNMPv3 SSHv2 Physical properties- Slots: 5- Housing: Metal- Dimensions: 205.65 x 133.35 x 100 mm (8.1 x 5.25 x 3.94 in.)- Weight: 2.560 g (5.64 lb)- Installation: Wall mounting (with optional kit) Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Relative humidity: 5 to 95% (non-condensing)- Altitude: 2000 m Standards and certifications- EMC: EN 55032/35 EN 61000-6-2/-6-4- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 5100 MHz to 6000 MHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Railway: EN 50121-4 EN 50155- Safety: UL 508- Shock: IEC 60068-2-27- Vibration: IEC 60068-2-6 MTBF- Time: ioPAC 8600-CPU30 models (HW Rev 1.0.1): 1,358,656 hours ioPAC 8600-CPU30 models (HW Rev 1.1.0): 1,273,872 hours ioPAC 8600-PW10-15W-T: 1,752,960 hours ioPAC 8600-PW10-30W-T: 1,341,777 hours ioPAC 8600-BM005-T: 2,678,587 hours ioPAC 8600-BM009-T: 1,350,621 hours ioPAC 8600-BM012-T: 1,238,479 hours- Standards: Telcordia SR332

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

