

Item no.: 387579

SPL-24-T - PoE splitter with a maximum output of 12.95 W at 24 VDC

from **217,78 EUR**

Item no.: 387579
shipping weight: 0.10 kg
Manufacturer: MOXA



Product Description

Moxa PoE splitters enable non-PoE powered devices (PD) to be coupled with PoE power sourcing equipment (PSE) by splitting the power from PoE to Ethernet devices. PoE splitter with maximum power of 12.95 W at 24 VDC, -40 to 75°C operating temperature Ethernet interface- 10/100BaseT(X) ports (RJ45 connector): 1 Full/half-duplex mode Auto MDI/MDI-X connection Automatic speed negotiation- PoE ports (PD), 10/100BaseT(X), RJ45 connection: 1 Full/half-duplex mode Auto MDI/MDI-X connection Automatic speed negotiation- Standards: IEEE 802.3af for PoE IEEE 802.3 for 10BaseT IEEE 802.3u for 100BaseT(X) Performance parameters- Operating voltage: 44 to 75 VDC (PoE)- Overload current protection: Supported- Rated output voltage: 24 VDC- Rated output power: 12.95 W (max.)- Connection: 1 removable 3-contact terminal block(s) Physical characteristics- Dimensions: 24.9 x 100 x 86.2 mm (0.98 x 3.93 x 3.39 in.)- Mounting: DIN rail mounting- Degree of protection: IP30- Weight: 95 g (0.21 lb) Environmental conditions- Operating temperature: -40 to 75°C (-40 to 167°F)- Storage temperature (including packaging): -40 to 85°C (-40 to 185°F)- Ambient relative humidity: 5 to 95% (non-condensing) Standards and certifications- Safety: UL 60950-1- EMC: EN 55032/24- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz; 10 V/m IEC 61000-4-4 EFT: Signal: 2 kV IEC 61000-4-5 Surge: Signal: 1 kV IEC 61000-4-6 CS: 10 V IEC 61000-4-8 PFMF- Free fall: IEC 60068-2-31- Shock: IEC 60068-2-27- Marine: DNV-GL, ABS, LR, NK- Vibration: IEC 60068-2-6 MTBF- Time: 5,104,703 hours- Standards: MIL-HDBK-217F

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

