

Item no.: 387852

EDS-308-S-SC-80 - Unmanaged Ethernet switch with 7 10/100BaseT(X) ports

from **951,42 EUR**

Item no.: 387852
shipping weight: 0.80 kg
Manufacturer: MOXA



Product Description

Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connection for 80 km transmission, relay output warning, 0 to 60 °C operating temperatureInput/output interfaceAlarm contact channels- 1 relay output with a current carrying capacity of 1 A @ 24 VDCEthernet interface10/100BaseT(X) ports (RJ45 connection)- 7- Automatic speed negotiation- Full/half-duplex mode- Automatic MDI/MDI-X connection100BaseFX ports (single-mode SC connection, 80 km)- 1Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.3x for flow controlDIP switch configurationEthernet interface- Port break alarmSwitch propertiesMAC table size- 2 kbitsPacket buffer size- 768 KProcessing type- Store and ForwardPower supply parametersInput current- 0.12 A @ 24 VDCConnection- 1 removable 6-contact terminal block(s)Operating voltage- 9.6 to 60 VDCInput voltage- Redundant dual inputs- 12/24/48 VDCReverse polarity protection- SupportsOverload current protection- SupportsPhysical propertiesHousing- MetallIP protection class- IP30Dimensions- 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)Weight- 790 g (1.75 lb)Installation- DIN rail mounting- Wall mounting (with optional kit)Ambient conditionsOperating temperature- -10 to 60°C (14 to 140°F)Storage temperature (including packaging)- -40 to 85°C (-40 to 185°F)Ambient relative humidity- 5 to 95% (non-condensing)Standards and certificationsSafety- UL 508- UL 60950-1- CSA C22.2 No. 60950-1- EN 62368 (LVD)EMC- EN 55032/35EMI- CISPR 32, FCC Part 15B Class AEMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 MHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 VHzazardous areas- ATEX- Class I Division 2Vibration- IEC 60068-2-6Shock- IEC 60068-2-27Free fall- IEC 60068-2-32Maritime- DNVMTBFTIME- 2.646,710 hrsStandards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

